



Avaya Call Management System
Open Database Connectivity
Version 4.2

585-780-701
Issue 2.0
May 2005

© 2005 Avaya Inc.
All Rights Reserved.

Notice

While reasonable efforts were made to ensure that the information in this document was complete and accurate at the time of printing, Avaya Inc. can assume no liability for any errors. Changes and corrections to the information in this document may be incorporated in future releases.

Documentation disclaimer

Avaya Inc. is not responsible for any modifications, additions, or deletions to the original published version of this documentation unless such modifications, additions, or deletions were performed by Avaya. Customer and/or End User agree to indemnify and hold harmless Avaya, Avaya's agents, servants and employees against all claims, lawsuits, demands and judgments arising out of, or in connection with, subsequent modifications, additions or deletions to this documentation to the extent made by the Customer or End User.

Link disclaimer

Avaya Inc. is not responsible for the contents or reliability of any linked Web sites and does not necessarily endorse the products, services, or information described or offered within them. We cannot guarantee that these links will work all of the time and we have no control over the availability of the linked pages.

Warranty

Avaya Inc. provides a limited warranty on this product. Refer to your sales agreement to establish the terms of the limited warranty. In addition, Avaya's standard warranty language, as well as information regarding support for this product, while under warranty, is available through the following Web site:

<http://www.avaya.com/support>

Preventing toll fraud

"Toll fraud" is the unauthorized use of your telecommunications system by an unauthorized party (for example, anyone who is not a corporate employee, agent, subcontractor, or person working on your company's behalf). Be aware that there may be a risk of toll fraud associated with your system and that, if toll fraud occurs, it can result in substantial additional charges for your telecommunications services.

Avaya fraud intervention

If you suspect that you are being victimized by toll fraud and you need technical assistance or support, call Technical Service Center Toll Fraud Intervention Hotline at +1-800-643-2353 for the United States and Canada. For additional support telephone numbers, see the Avaya Web site:

<http://www.avaya.com/support>

Providing telecommunications security

Telecommunications security (of voice, data, and video communications) is the prevention of any type of intrusion to (that is, either unauthorized or malicious access to or use of) your company's telecommunications equipment by some party.

Your company's "telecommunications equipment" includes both this Avaya product and any other voice/data/video equipment that could be accessed via this Avaya product (that is, "networked equipment").

An "outside party" is anyone who is not a corporate employee, agent, subcontractor, or person working on your company's behalf. Whereas, a "malicious party" is anyone (including someone who may be otherwise authorized) who accesses your telecommunications equipment with either malicious or mischievous intent.

Such intrusions may be either to/through synchronous (time-multiplexed and/or circuit-based) or asynchronous (character-, message-, or packet-based) equipment or interfaces for reasons of:

- Use (of capabilities special to the accessed equipment)
- Theft (such as, of intellectual property, financial assets, or toll-facility access)
- Eavesdropping (privacy invasions to humans)
- Mischief (troubling, but apparently innocuous, tampering)
- Harm (such as harmful tampering, data loss or alteration, regardless of motive or intent)

Be aware that there may be a risk of unauthorized intrusions associated with your system and/or its networked equipment. Also realize that, if such an intrusion should occur, it could result in a variety of losses to your company (including, but not limited to, human and data privacy, intellectual property, material assets, financial resources, labor costs, and legal costs).

Your responsibility for your company's telecommunications security

The final responsibility for securing both this system and its networked equipment rests with you, an Avaya customer's system administrator, your telecommunications peers, and your managers. Base the fulfillment of your responsibility on acquired knowledge and resources from a variety of sources, including, but not limited to:

- Installation documents
- System administration documents
- Security documents
- Hardware-/software-based security tools
- Shared information between you and your peers
- Telecommunications security experts

To prevent intrusions to your telecommunications equipment, you and your peers should carefully program and configure:

- Your Avaya-provided telecommunications systems and their interfaces
- Your Avaya-provided software applications, as well as their underlying hardware/software platforms and interfaces
- Any other equipment networked to your Avaya products.

Trademarks

Avaya is a trademark of Avaya Inc.

Multivantage and DEFINITY are registered trademarks of Avaya Inc. All non-Avaya trademarks are the property of their respective owners.

Document ordering information:

Avaya Publications Center

Voice: +1-207-866-6701
1-800-457-1764 (Toll-free, U.S. and Canada only)

Fax: +1-207-626-7269
1-800-457-1764 (Toll-free, U.S. and Canada only)

Write: Globalware Solutions
200 Ward Hill Avenue
Haverhill, MA 01835 USA
Attention: Avaya Account Manager

Web: <http://www.avaya.com/support>

E-mail: totalware@gwsmail.com

Order: Document No. 585-780-701, Issue 2.0
May 2005

For the most current versions of documentation, go to the Avaya support Web site:

<http://www.avaya.com/support>

Avaya support

Avaya provides a telephone number for you to use to report problems or to ask questions about your contact center. The support telephone number is 1-800-242-2121 in the United States. For additional support telephone numbers, see the Avaya Web site:

<http://www.avaya.com/support>

**Avaya Call Management System
Open Database Connectivity
Version 4.2**

Contents

| | |
|--|-----------|
| Preface | 7 |
| Purpose | 8 |
| Intended users | 8 |
| Overview | 8 |
| Conventions and terminology | 9 |
| Reasons for reissue | 9 |
| Availability | 10 |
| Related documentation | 11 |
| Change description | 11 |
| Software documents | 11 |
| Administration documents | 12 |
| Hardware documents | 12 |
| Call Center documents | 12 |
| Avaya CMS upgrade documents | 13 |
| Base load upgrades | 13 |
| Platform upgrades and data migration | 13 |
| Avaya Call Management System Upgrade Express (CUE) | 13 |
| Documentation Web sites | 14 |
| Support | 15 |
| About Open Database Connectivity | 17 |
| ODBC background and functionality | 17 |
| Data access through ODBC | 18 |
| Data access diagram | 18 |
| Structured query language | 19 |
| CMS support of ODBC | 19 |
| ODBC driver functionality | 20 |
| Uses for ODBC data | 20 |
| Requesting data using ODBC | 20 |
| About the ODBC driver | 21 |
| ODBC features | 22 |
| Languages | 22 |
| Supported logins | 22 |
| Queries | 22 |
| Performance impact | 23 |
| Table permissions, security and port allocation | 24 |

Contents

| | |
|--|-----------|
| CMS feature interactions that require client support | 24 |
| ODBC installation | 27 |
| Things to consider when different ODBC versions are in use | 28 |
| Openlink ODBC compatibility table | 29 |
| Installing ODBC on the CMS server | 30 |
| System requirements | 30 |
| Determining the CMS version | 30 |
| Installing the ODBC 4.2 server software | 31 |
| Using the server utilities | 35 |
| Setting debug levels | 35 |
| Setting log levels | 35 |
| Turning ODBC on or off | 36 |
| Installing ODBC 4.2 on a Solaris client | 37 |
| System requirements | 37 |
| Installing ODBC on the Solaris client | 37 |
| Configuring ODBC drivers on the Solaris client | 41 |
| Testing ODBC connectivity on a Solaris client | 44 |
| About building an ODBC application on a Solaris client | 45 |
| Installing ODBC 4.2 on a Windows client | 46 |
| System requirements | 46 |
| Installing the ODBC client on a Windows client | 46 |
| Installing clients over the network | 48 |
| Configuring ODBC drivers on a Windows client | 49 |
| Prerequisites | 49 |
| Description of the ODBC Data Source Administrator window | 50 |
| Description of the OpenLink ODBC Setup window | 51 |
| Configuring an ODBC server data source | 53 |
| Accessing the ODBC Data Source Administrator window | 55 |
| Accessing the ODBC Data Source Administrator window with Windows 98, Windows 2000, or Windows NT 4.0 | 56 |
| Accessing the ODBC Data Source Administrator window with Windows XP | 56 |
| Configuring a user data source | 56 |
| Removing a data source | 57 |
| Configuring ODBC tracing options | 57 |
| Viewing installed ODBC data source drivers | 59 |
| Testing ODBC connectivity on a Windows client | 60 |
| Connecting to and accessing data | 60 |
| Disconnecting from a data source | 63 |
| Troubleshooting | 65 |
| Clients cannot connect to the ODBC server | 66 |
| Multiple connections with the same username | 66 |
| Network support | 67 |
| Server log file | 67 |

| | |
|--|-----------|
| Client trace | 67 |
| Possible failure causes for a test application error | 68 |
| OpenLink error messages | 69 |
| Database tables | 71 |
| Things to consider when using ODBC | 71 |
| CMS database logic structure | 72 |
| Agent tables | 72 |
| VDN tables | 72 |
| Circular structure tables | 73 |
| CMS database table names | 73 |
| Description of the CMS database tables | 76 |
| About the Database item column | 76 |
| Index database items | 76 |
| Call-based data and interval-based data | 76 |
| About the Data types column | 77 |
| About the Column type and Length columns | 77 |
| Informix data column types table | 78 |
| CMS database table items | 79 |
| Agent database items | 79 |
| Agent Login/Logout database items | 90 |
| Agent Trace database items | 91 |
| Call Record database items | 94 |
| Call Work Codes database items | 96 |
| Exceptions historical database items | 97 |
| Agent Exceptions database items | 98 |
| Split/Skill Exceptions database items | 99 |
| Trunk Group Exceptions database items | 99 |
| VDN Exceptions database items | 100 |
| Vector Exceptions database items | 101 |
| Malicious Call Trace Exceptions database items | 101 |
| Data Collection Exceptions database items | 102 |
| Disk Full Exceptions database items | 103 |
| Split/Skill database items | 103 |
| Trunk Group database items | 111 |
| Trunk database items | 116 |
| Vector database items | 119 |
| VDN database items | 122 |
| Forecasting database tables | 129 |
| Current Day Configuration database items | 129 |
| Current Day Report database items | 130 |
| Administrative database tables | 131 |
| Data Collection Period database items | 132 |
| Archiver Execution Status database items | 133 |
| Customer Log database items | 133 |
| Agent Group database items | 134 |
| Synonyms database items | 135 |
| ACD Shifts database items | 136 |

Contents

| | |
|---|------------|
| Database Items | 136 |
| Generating a CMS database schema | 138 |
| Generating the schema for the entire CMS database | 138 |
| About the dbschema command | 139 |
| Glossary | 141 |
| Index | 147 |



Preface

Avaya Call Management System (CMS) is an application for businesses and organizations that use Avaya communication servers to process large volumes of telephone calls using the Automatic Call Distribution (ACD) feature. Avaya CMS supports solutions for routing and agent selection, multi-site contact centers, remote agents, reporting, interfaces to other systems, workforce management, desktop applications, system recovery, and quality monitoring.

Open Database Connectivity (ODBC) is an optional Avaya Call Management System (CMS) feature that allows you to access data in the CMS database for use in other software applications, such as spreadsheet programs. With ODBC, you can access the CMS data directly from your application without the need to understand database connectivity or format.

Avaya CMS is part of the Operational Effectiveness solution of the Avaya Customer Interaction Suite.

This section includes the following topics:

- [Purpose](#) on page 8
- [Intended users](#) on page 8
- [Overview](#) on page 8
- [Conventions and terminology](#) on page 9
- [Reasons for reissue](#) on page 9
- [Availability](#) on page 10
- [Related documentation](#) on page 11
- [Support](#) on page 15

Purpose

The purpose of this document is to describe how to use ODBC. This document will help users decide which database items to use in custom reports, spreadsheets, and other user applications that require external data access.

Intended users

This document is written for:

- Avaya support personnel
- Contact center administrators

Users of this document must be familiar with Avaya CMS, have a basic understanding of SQL, and have a basic understanding of database logic and purpose.

Overview

This document includes the following topics:

- [About Open Database Connectivity](#) on page 17
Presents an overview of the ODBC feature, its interaction with other CMS features, and its performance impact.
- [ODBC installation](#) on page 27
Presents basic installation, configuration, and initialization procedures for the driver on the server and the clients.
- [Troubleshooting](#) on page 65
Presents troubleshooting information for the ODBC feature.
- [Database tables on page 71](#)
Describes the CMS open database tables and the items in the database tables.

Conventions and terminology

If you see any of the following safety labels in this document, take careful note of the information presented.

**CAUTION:**

Caution statements call attention to situations that can result in harm to software, loss of data, or an interruption in service.

**WARNING:**

Warning statements call attention to situations that can result in harm to hardware or equipment.

**DANGER:**

Danger statements call attention to situations that can result in harm to personnel.

**SECURITY ALERT:**

Security alert statements call attention to situations that can increase the potential for unauthorized use of a telecommunications system.

Reasons for reissue

This document differs from the previous issue in the following ways:

- Added a new procedure to the Troubleshooting section. For more information, see [Multiple connections with the same username](#) on page 66.
- Made general updates for CMS R13.

Availability

Copies of this document are available from one or both of the following sources:

Note:

Although there is no charge to download documents through the Avaya Web site, documents ordered from the Avaya Publications Center must be purchased.

- The Avaya online support Web site, <http://www.avayadocs.com>
- The Avaya Publications Center, which you can contact by:

Voice:

+1-207-866-6701

+1-800-457-1764 (Toll-free, U.S. and Canada only)

Fax:

+1-207-626-7269

+1-800-457-1764 (Toll-free, U.S. and Canada only)

Mail:

GlobalWare Solutions
200 Ward Hill Avenue
Haverhill, MA 01835 USA
Attention: Avaya Account Manager

E-mail:

totalware@gwsmail.com

Related documentation

You might find the following Avaya CMS documentation useful. This section includes the following topics:

- [Change description](#) on page 11
- [Software documents](#) on page 11
- [Administration documents](#) on page 12
- [Hardware documents](#) on page 12
- [Call Center documents](#) on page 12
- [Avaya CMS upgrade documents](#) on page 13
- [Documentation Web sites](#) on page 14

Change description

For information about the changes made in Avaya CMS R13, see:

- *Avaya Call Center 3.0 and Call Management System (CMS) Release 13 Change Description*, 07-300304

Software documents

For more information about Avaya CMS software, see:

- *Avaya Call Management System Release 13 Software Installation, Maintenance, and Troubleshooting Guide*, 07-300340
- *Avaya CMS Open Database Connectivity Version 4.2*, 585-780-701
- *Avaya Call Management System Release 13 LAN Backup User Guide*, 07-300338
- *Avaya Call Management System Release 13 External Call History Interface*, 07-300332
- *Avaya CMS Custom Reports*, 585-215-822
- *Avaya CMS Forecast User Guide*, 585-215-825
- *Avaya Visual Vectors Release 13 Installation and Getting Started*, 07-300353
- *Avaya Visual Vectors Release 13 User Guide*, 07-300354
- *Avaya Call Management System (CMS) Supervisor Release 13 Report Designer*, 07-300335

Administration documents

For more information about Avaya CMS administration, see:

- *Avaya Call Management System Release 13 Administration*, 07-300331
- *Avaya Call Management System (CMS) Release 13 Database Items and Calculations*, 07-300330
- *Avaya Call Management System Supervisor Release 13 Reports*, 07-300334
- *Avaya Call Management System (CMS) Supervisor Release 13 Installation and Getting Started*, 07-300333
- *Avaya Call Management System High Availability User Guide*, 07-300066
- *Avaya Call Management System High Availability Connectivity, Upgrade and Administration*, 07-300065

Hardware documents

For more information about Avaya CMS hardware, see:

- *Avaya Call Management System Sun Fire V880/V890 Computer Hardware Installation, Maintenance, and Troubleshooting*, 585-215-116
- *Avaya Call Management System Sun Blade 100/150 Workstation Hardware Installation, Maintenance, and Troubleshooting*, 585-310-783
- *Avaya Call Management System Terminals, Printers, and Modems*, 585-215-874

Call Center documents

For more information about Avaya Call Center documents, see:

- *Avaya Communication Manager Call Center Software Basic Call Management System (BCMS) Operations*, 07-300061
- *Avaya Call Management System Switch Connections, Administration, and Troubleshooting*, 585-215-876
- *Avaya Communication Manager Call Center Software Call Vectoring and Expert Agent Selection (EAS) Guide*, 07-300303
- *Avaya Communication Manager Call Center Software Automatic Call Distribution (ACD) Guide*, 07-300301
- *Avaya Business Advocate Release 13 User Guide*, 07-300336

Avaya CMS upgrade documents

There are several upgrade paths supported with Avaya CMS. There is a document designed to support each upgrade.

This section includes the following topics:

- [Base load upgrades](#) on page 13
- [Platform upgrades and data migration](#) on page 13
- [Avaya Call Management System Upgrade Express \(CUE\)](#) on page 13

Base load upgrades

Use a base load upgrade when upgrading CMS to the latest load of the same version (for example, r13ak.g to r13al.k). A specific set of instructions is written for the upgrade. The instructions are shipped to the customer site with the CMS software CD-ROM as part of a Product Correction Notice (PCN).

For more information about base load upgrades, see:

- *Avaya Call Management System Release 13 Base Load Upgrade*

Platform upgrades and data migration

Use a platform upgrade when upgrading to a new hardware platform (for example, upgrading from a SPARCserver 5 to a Sun Blade 150). The new hardware platform is shipped from the Avaya factory with the latest CMS load. Therefore, as part of the upgrade you will have the latest CMS load (for example, R3V9 to R13).

For more information about platform upgrades and data migration, see:

- *Avaya Call Management System Release 13 Platform Upgrade and Data Migration, 07-300339*

Avaya Call Management System Upgrade Express (CUE)

Use CUE when CMS is being upgraded from an earlier version (for example, R3V9) to the latest version (for example, R13).

A specific set of upgrade instructions is written for the upgrade. These instructions are included on the CUE software CD-ROM that is shipped to the customer site with the CUE kit.

For information about customer requirements for CUE upgrades, see:

- *Avaya Call Management System Release 13 CMS Upgrade Express (CUE) Customer Requirements, 700356744*

Preface

For information about CUE upgrade procedures, see:

- *Avaya Call Management System Release 13 Sun Blade 100/150 Workstation Mirrored and Nonmirrored Systems CMS Upgrade Express (CUE)*, 07-300481
- *Avaya Call Management System Release 13 Sun Fire V880/V890 Computer CMS Upgrade Express (CUE)*, 07-300344

Documentation Web sites

For Avaya product documentation, go to <http://www.avayadocs.com>. Additional information about new software or hardware updates will be contained in future issues of this book. New issues of this book will be placed on the Web site when available.

Use the following Web sites to view related support documentation:

- Information about Avaya products and service
<http://www.avaya.com>
- Sun hardware documentation
<http://docs.sun.com>
- Informix documentation
<http://www.informix.com>
- Tivoli Storage Manager documentation
<http://www.tivoli.com>

Support

Contacting Avaya technical support

Avaya provides support telephone numbers for you to report problems or ask questions about your product.

For United States support:

1- 800- 242-2121

For international support:

See the [1-800 Support Directory](#) listings on the Avaya Web site.

Escalating a technical support issue

Avaya Global Services Escalation Management provides the means to escalate urgent service issues. For more information, see the [Escalation Management](#) listings on the Avaya Web site.

■ ■ ■ ■ ■ ■

About Open Database Connectivity

This section presents an overview of how Open Database Connectivity (ODBC) works and how it interacts with the Avaya Call Management System (CMS).

This section contains the following topics:

- [ODBC background and functionality](#) on page 17
- [About the ODBC driver](#) on page 21
- [ODBC features](#) on page 22

ODBC background and functionality

The ODBC feature is a client/server feature. To access the server the clients must be connected to a network that is fully functional and able to access the server. The *clients* are the computers that are accessing data through ODBC. The *server* is the CMS machine where the CMS database is located.

The ODBC feature is especially useful for call centers with multiple sites. ODBC allows access to data at multiple sites. You can use this data to produce reports. ODBC uses Structured Query Language (SQL) to access data.

ODBC is an Application Programming Interface (API) that allows you to access one or many Database Management Systems (DBMSs). You can use queries to access data in the database for use in reports and other outside applications.

This section contains the following topics:

- [Data access through ODBC](#) on page 18
- [Structured query language](#) on page 19
- [CMS support of ODBC](#) on page 19
- [Uses for ODBC data](#) on page 20
- [Requesting data using ODBC](#) on page 20


Data access through ODBC

ODBC was developed as a way to access different types of data. A single call center may be working with different applications that must access call center data. For example, a call center could be using Microsoft Access.

ODBC provides a standard method of database access without users having to be concerned with the underlying functionality of network software, naming conventions, and other complexities involved in accessing data through a DBMS. The data must be queried through the embedded SQL query function in the application that you are using. Refer to your specific application documentation for further information on the embedded SQL function for that particular application.

Data access diagram

The following figure illustrates user data access through ODBC.



⚠ Important:

Avaya will support only ODBC connectivity. Avaya will not support third-party client applications, such as Microsoft Access, or Windows.

Structured query language

ODBC uses Structured Query Language (SQL) to query and access data. Because SQL is a language, queries written in SQL can be used to access data with different formats. SQL is the basis for relational database access.

A relational database model is a table that stores data in rows and columns. Relationships between tables are established through data items that match data item values in another table.

SQL queries access the data stored in the relational database tables and extracts it for use in other applications. You compose an SQL query in the Windows application for which you need the data.

You can also use SQL to construct data calculations. You can use data calculations to see a sum of the data. For example, you can view the total number of calls routed to a particular split or skill.

CMS support of ODBC

The Informix database management system (DBMS) used by CMS is supported by the OpenLink Multi-Tier ODBC driver. The driver is an implementation of an ODBC application programming interface (API) that supports a particular database management system.

A driver is a dynamic link library (DLL) that is specific to a type of DBMS. The driver manager provides the link between the user's applications and the DBMS itself. When you run a query, the DBMS makes the link by selecting the DLL with the appropriate data format.

 **Important:**

If you choose to develop an application for the ODBC driver, Avaya cannot provide support for that application or for any other third-party software or related mapping.


For more information about the OpenLink driver, see [About the ODBC driver](#) on page 21.

Note:

Avaya tests ODBC only in English. ODBC version 4.2 will support other double-byte languages, but if you use a language other than English, Avaya cannot provide ODBC support.

ODBC driver functionality

The following figure illustrates how the driver provides the interface between client applications and the data being accessed in the server.



Uses for ODBC data

Data extracted and stored by an ODBC application can be used by ODBC-enabled programs, such as workforce management packages, network routers, and blended inbound/outbound applications. You can use an ODBC data application to generate reports using data from multiple call center sites and their databases.

Requesting data using ODBC

All queries in ODBC must be composed so that they ensure continued CMS performance. The query is invoked differently in each Windows application.

For more information on how to compose efficient database queries, see [Performance impact](#) on page 23 and the chapter on editing queries in the appropriate Avaya CMS Supervisor report designer user guide.

For more information on how your application interfaces with ODBC, refer to the user documentation for your application.

About the ODBC driver

The OpenLink ODBC driver has two main components:

- A generic ODBC driver
- OpenLink Request Agent

The OpenLink ODBC driver is a multi tier driver. The driver controls both ODBC calls and the manner in which these calls are transferred over the communications infrastructure to the relevant database management system.

The OpenLink Request Broker provides the link between the user's applications and the database management system. After ODBC is installed and administered, the ODBC driver and its components are transparent to the client. The CMS ODBC feature allows multiple, synchronous accesses from clients, users, and applications.

The OpenLink Request Agent resides on the client and interfaces with the ODBC driver through proprietary protocol. ODBC drivers are controlled by an ODBC driver manager, which is the OpenLink Request Broker. The OpenLink Request Broker resides on the server. ODBC uses data source names as the link between the ODBC Request Broker and the relevant ODBC driver for a particular database.

For additional information on the ODBC driver, see the online Help file that is included on the CMS OpenLink ODBC driver CD-ROM.

ODBC features

An OpenLink ODBC driver provides the ODBC communication and connectivity that allows external data access to the CMS database. There are individual drivers that support Solaris, Windows 98, Windows 2000, Windows XP, and Windows NT 4.0 clients. All historical CMS database tables, dictionary tables, and customer-provided tables can be accessed by ODBC clients through standard ODBC-enabled software applications.

All standard Structured Query Language (SQL) queries generated by the user applications are supported by the ODBC driver, as limited by permissions. Table-level, read-only permissions restrict access to certain database tables.

This section contains the following topics:

- [Languages](#) on page 22
- [Supported logins](#) on page 22
- [Queries](#) on page 22
- [Performance impact](#) on page 23
- [Table permissions, security and port allocation](#) on page 24
- [CMS feature interactions that require client support](#) on page 24

Languages

Avaya tests ODBC only in English for use with CMS. ODBC version 4.2 will support other double-byte languages, but if you use a language other than English, Avaya does *not* provide ODBC support for that language.

Supported logins

Depending on your licensing agreement, the CMS ODBC feature supports either five or ten simultaneous logins. Additional logins can be added in increments of five.

Queries

You can generate queries from client to server and from user applications. The ODBC driver is installed on the server, and the accompanying software is installed on the clients. The extracted data can be used in workforce management packages, network routers, and

blended inbound or outbound applications. Any application that supports ODBC functionality can access tables with the proper table permissions. For example, one of the tables that could be accessed is the CMS Dictionary.

For more information on how to compose efficient database queries, see the chapter on editing queries in the appropriate Avaya Supervisor report designer user guide.

Performance impact

The number, size, and types of queries received by the CMS may impact performance. The recommendations for composing queries in the CMS custom report editor also apply to ODBC queries. Some of the activities that may impact on CMS performance are:

Tables - Use the exact table and database item names when querying the database. You can maximize the performance of the system by running queries that access large tables or that perform table joins during a period of low agent activity and low real-time report activity. Accessing large tables, such as the split/skill or agent tables, or joining tables in queries may have a negative impact on CMS performance.

Calculations - Review calculations before sending them to the database. This ensures that the correct operation is performed. Arithmetic operations are performed with the rules of operator precedence, in order from left to right. The operator precedence is shown in the following table:

| Precedence | Arithmetic operations |
|------------|-----------------------|
| 1 | () [] |
| 2 | * / % |
| 3 | + - |

Queries - Prioritize resource intensive queries the same way you prioritize reports during high business activity. Running complex or multiple queries on the database impact system performance similar to running multiple reports.

Number of simultaneous database accesses - Minimize the number of database connects and disconnects from an application, and spread your ODBC activities throughout the day.

Synonyms - Download the synonyms to your client application or database and then perform the join at the client.

CMS maintenance - Be aware that during off-peak hours, CMS runs its own activities, such as archiving and making backups. This can use a significant amount of resources and time when working with a large database.

Table permissions, security and port allocation

ODBC users log into the CMS server with password protection. Users have SQL access to Informix tables, as limited by the table permissions. The database tables that are accessible in a particular version of CMS are described in detail in [Database tables on page 71](#).

All historical and dictionary database tables have read-only access permission. The customer-created tables (any table name that begins with "c_") on the host have read and write permissions. No other tables are accessible through ODBC.

 **Important:**

If your network uses a fire wall, it is common for unused ports to be locked. ODBC uses UDP port 60001 and the TCP ports between PortLow and PortHigh. If these ports are locked, you will not be able to connect to the CMS database with ODBC.

Depending on the ODBC version, the ports will be defined under [Protocol TCP] in one of the following files:

| CMS version | Openlink version | File location |
|-------------------|------------------|---|
| R3V6, R3V8 | 3.2 or 4.2 | <i>/cms/dc/odbc/cmsrqb3.2_init</i> ¹ |
| R3V9aj and later | 4.2 | <i>/cms/dc/odbc/cmsrqb4.2_init</i> |
| R3V11af and later | 4.2 | <i>/cms/dc/odbc/cmsrqb4.2_init</i> |

1. When you install the Openlink 4.2 driver on a CMS R3V6 or CMS R3V8 system, the system will contain a **cmsrqb3.2_init** file instead of a **cmsrqb4.2_init** file. This is normal.

CMS feature interactions that require client support

Some CMS features require specific client administration and interaction. The data received by the client application is in raw form. You must format raw data for use within your application. Dictionary names and certain time fields are most affected by this formatting.

Dictionary names - Clients can access CMS dictionary names. The client must map the synonym to the report. Underlying data is numeric. For example, different splits are stored as numbers and not by their names.

Permissions - Applications that access Informix externally, such as database access scripts, may not work if the table permission script tries to access a table to which permission is denied. CMS-like permissions to individual entities, such as splits and vectors, are not available through the ODBC interface. It is up to the client application to create and enforce permissions at this level if this is required.

Field Display - The time and date data received from the database may not be formatted. The time is usually shown in seconds or in military format. Review data for formatting when importing it into your software application. See your software's documentation for further information on formatting data.

For more information on data format and values, see [Database tables on page 71](#).

■ ■ ■ ■ ■ ■ ODBC installation

This section presents basic installation, configuration, initialization, and connection procedures for the ODBC software. All necessary files for the server and client installation are included on the CMS OpenLink ODBC driver CD-ROM.

OpenLink ODBC driver installation and configuration procedures are for the CMS server, Sun Solaris clients, and Windows clients. Use the installation and configuration procedures that are specific to your client and server environment. Installation on your server will not impact system performance. The ODBC server components may be installed at any time.

This section contains the following topics:

- [Things to consider when different ODBC versions are in use](#) on page 28
- [Installing ODBC on the CMS server](#) on page 30
- [Using the server utilities](#) on page 35
- [Installing ODBC 4.2 on a Solaris client](#) on page 37
- [Configuring ODBC drivers on the Solaris client](#) on page 41
- [Testing ODBC connectivity on a Solaris client](#) on page 44
- [About building an ODBC application on a Solaris client](#) on page 45
- [Installing ODBC 4.2 on a Windows client](#) on page 46
- [Configuring ODBC drivers on a Windows client](#) on page 49
- [Testing ODBC connectivity on a Windows client](#) on page 60

Things to consider when different ODBC versions are in use

Different versions of the ODBC software are supported with different CMS loads. It is possible that different call center locations may be using different versions of the ODBC software. Refer to the [Openlink ODBC compatibility table](#) on page 29 for information about ODBC settings for different versions of CMS.

Avaya recommends that you use the corresponding ODBC driver versions for the client and server to ensure connectivity. For example, if your server uses the ODBC 4.2 server your client must use the ODBC 4.2 client.

The ODBC 4.2 client will connect to an ODBC 3.2 server if the OpenLink Generic 32 bit driver is loaded in addition to the Generic 32 bit v4.0 driver. An ODBC 3.2 client will not connect to an ODBC 4.2 server. If you need information about an earlier version of the ODBC software, refer to the original user documentation for that software.

Openlink ODBC compatibility table

Use the following table to determine CMS and ODBC compatibility.

| | CMS R3V6 or R3V8 (any version) | CMS R3V9 versions earlier than R3V9aj ¹ | CMS R3V11 versions earlier than R3V11af | CMS R3V9aj or later | CMS R3V11af or later |
|---|-----------------------------------|---|--|---------------------------------|---------------------------------|
| Openlink ODBC version | 3.2 or 4.2 | 3.2 | 3.2 | 4.2 | 4.2 |
| Solaris OS version | 5.5.1 or 5.7 | 5.8 | 5.8 | 5.8 | 5.8 |
| Solaris ODBC client version | 2.5 or 2.6 | 2.5 or 2.6 | 2.5 or 2.6 | 2.8 | 2.8 |
| Informix provider type or Informix database domain name (Used by Windows client) | 7.3 | 7.3 | 7.3 | 2000 | 2000 |
| CMS database path | /cms/db/inf/cms | cms | cms | cms | cms |
| Informix server type (Used by Solaris client) | 7 | 7 | 7 | 2000 | 2000 |
| Openlink data source driver | ODBC Generic Driver 32 Bit | ODBC Generic Driver 32 Bit | ODBC Generic Driver 32 Bit | ODBC Generic Driver 32 Bit v4.0 | ODBC Generic Driver 32 Bit v4.0 |

1. If you are running an earlier load of R3V9 or R3V11 CMS, you must upgrade your system before you can use ODBC version 4.2. Depending on your current CMS version, the upgrade would be either a base load upgrade or CUE upgrade.

Installing ODBC on the CMS server

This section describes system requirements, software installation procedures, and configuration procedures for the OpenLink Multi-Tier ODBC driver on the CMS server.

This section contains the following procedures:

- [System requirements](#) on page 30
- [Determining the CMS version](#) on page 30
- [Installing the ODBC 4.2 server software](#) on page 31

System requirements

The following system requirements must be met before you install the software:

- The ODBC version 4.2 server must be on a standard CMS hardware platform with Solaris version 5.5.1 or later.
- The server must have one of the following CMS loads installed:
 - R3V6
 - R3V8
 - R3V9aj or later
 - R3V11af or later
- The network communication software must be correctly installed and configured, and the network must be fully functional so that the server can communicate with the clients.

Determining the CMS version

Before installing the OpenLink ODBC driver on the server, determine which version of CMS is installed.

To determine the CMS version:

1. On the CMS system, enter:

```
pkginfo -x cms
```

The system displays the CMS version information.

2. Record the CMS version so you can select the correct installation options.

Installing the ODBC 4.2 server software

To install ODBC on the CMS server:

1. Verify that you are installing the correct software for your CMS load. For more information, see [Determining the CMS version](#) on page 30 and the [Openlink ODBC compatibility table](#) on page 29.
2. Load the CD-ROM, *Avaya CMS OPENLINK ODBC Driver*.
3. Wait about 15 seconds. Then verify the name of the CD-ROM by entering:

```
mount
```

The system displays a list of devices and file systems currently mounted. On the last line, the system should display the installed CD-ROM similar to the message shown below:

```
/cdrom/openlink on /vol/dev/dsk/c0t2d0/openlink read only on (current  
date and time)
```

4. Enter:
5. Verify you are in **/usr** by entering:

```
pwd
```

The system displays the current working directory:

```
/usr
```

6. Choose one of the following procedures:
 - If this is *not* an upgrade of the ODBC software, go to Step 7.
 - If this is an upgrade of the ODBC software, perform the following steps:
 - i. Shut down the request broker by entering:

```
/cms/dc/odbc/odbc_init -r 0
```

- ii. Remove the old **openlink** directory by entering:

```
rm -fr /usr/openlink
```

7. Create the OpenLink directory and change to the new directory by entering the following commands:

```
mkdir /usr/openlink
```

```
cd /usr/openlink
```

ODBC installation

8. Verify that you are in **/usr/openlink** by entering:

```
pwd
```

9. Choose one of the following commands:

- If you are installing the software on a CMS R3V9 or later system enter:

```
cp /cdrom/cdrom0/server/cmsv9v11/* /usr/openlink
```

- If you are installing the software on a CMS R3V6 or CMS R3V8 system enter:

```
cp /cdrom/cdrom0/server/cmsv6v8/* /usr/openlink
```

10. Install the server components on the system by entering:

```
./install.sh
```

The system displays the following message:

```
Extracting (srmi9zz.taz) ...
.....
.....
.....
Enter the port number the the broker will listen on for
client connections [Enter=Default] :
```

11. Accept the default setting by pressing **Enter**.

The system displays the following message:

```
Welcome to the OpenLink Admin Assistant Setup.

This program will install the HTTP based OpenLink Admin Assistant,
thereby enabling remote configuration for all OpenLink Server
Components (Rule Book,
Service and Database Agents) from any Web Browser.

TCP/IP Port to use? [ENTER=8000] :
```

12. Accept the default setting by pressing **Enter**.

The system displays the following message:

```
Log File? [ENTER=www_sv.log]
```

13. Accept the default setting by pressing **Enter**.

The system displays the following message:

```
Log all requests (y/n)? [ENTER=n]
```

14. Accept the default setting by pressing **Enter**.

The system displays the following message:

```
Administrator account? [ENTER=admin]
```

15. Accept the default setting by pressing **Enter**.

The system displays the following message:

```
Administrator's password? [ENTER=admin]
```

16. Accept the default setting by pressing **Enter**.

The system displays the following message:

```
The OpenLink Admin Assistant is now ready for use.
.....
.....
.....
Enter the name of the user that will own the programs [ENTER=Use
Current User Settings] :
```

17. Enter:

```
root
```

The system displays the following message:

```
Enter the name of the group that will own the programs [ENTER=Use
Current Group Settings] :
```

18. Enter:

```
root
```

The system displays the following message:

```
Changing ownership ...
End of installation
```

19. Choose one of the following commands to configure and initiate the ODBC software:

- If this is a new installation, enter:

```
/cms/dc/odbc/odbc_init
```

The system displays the following message:

```
ODBC driver initialization complete.
```

ODBC installation

- If this is an upgrade or reinstallation, enter:

```
/cms/dc/odbc/odbc_init -r 1
```

The system displays the following message:

```
oplrqb has been activated
```

20. Verify that the ODBC Request Broker is active on the server by entering:

```
ps -ef | grep oplrqb
```

One of the displayed messages should show the oplrqb process running from the **/usr/openlink/bin** directory.

- If CMS R3V9 or later is installed, the system displays a message similar to the following:

```
root 1462 1459 0 14:41:38 ?
0:00 /usr/openlink/bin/oplrqb -f +configfile /cms/dc/odbc/
cmsrqb4.2_init +loglevel 5 +l
```

- If CMS R3V6 or CMS R3V8 is installed, the system displays a message similar to the following:

```
root 1462 1459 0 14:41:38 ?
0:00 /usr/openlink/bin/oplrqb -f +configfile /cms/dc/odbc/
cmsrqb3.2_init +loglevel 5 +l
```

If you do not see an *oplrqb* process running after completing Step 20, repeat the installation. If after reinstalling the software the process still does not start, call Avaya support.

Using the server utilities

After the ODBC driver is installed on the server, a CMS utility program is available for setting the debug and log levels, and for running and deactivating the ODBC feature using the run feature. This utility program is located in the `/cms/dc/odbc` directory.

This section contains the following procedures:

- [Setting debug levels](#) on page 35
- [Setting log levels](#) on page 35
- [Turning ODBC on or off](#) on page 36

Setting debug levels

To set the server ODBC debug level:

1. Enter:

```
cd /cms/dc/odbc
```

2. Enter:

```
./odbc_init -d x
```

where `x` is one of the following parameters:

- To turn off the debug utility, enter: 0
- To turn on the debug utility, enter: 1

Setting log levels

To set the CMS server log level for ODBC:

1. Change directories to `/cms/dc/odbc` by entering:

```
cd /cms/dc/odbc
```

2. Enter:

```
./odbc_init -l x
```

where `l` is the lowercase letter l, and

where `x` is one of the following log levels:

- 0 turns off the CMS server logging

ODBC installation

- 1 through 7 sets the log level, with 1 as the lowest level and 7 as the highest. The default and recommended setting is 5.

Note:

Avaya recommends that users not set the log level to a value greater than 5. Doing so could reduce performance. If you use the log level 7 (troubleshooting), make sure that the value is changed back to the default log level (5) after troubleshooting.

Turning ODBC on or off

To turn the ODBC feature on or off on the server:

1. Enter:

```
cd /cms/dc/odbc
```

2. Enter:

```
./odbc_init -r x
```

where **x** is one of the following parameters:

- To turn off the ODBC feature, enter: 0
- To turn on the ODBC feature, enter: 1

Installing ODBC 4.2 on a Solaris client

The OpenLink ODBC driver software can be installed on a Solaris client. The client software must be configured and tested for connectivity after it is installed.

This section contains the following topics:

- [System requirements](#) on page 37
- [Installing ODBC on the Solaris client](#) on page 37

System requirements

Before installing the OpenLink ODBC driver software on a Solaris client, you must:

- Verify that the client is communicating with the CMS server over the network.
Use the network protocol's ping utility to verify that communication between the client and the CMS server is functional. Do not proceed if basic communications between the client and the server cannot be established. If the client cannot recognize the network, the ODBC driver will not function properly.
- Verify that the ODBC clients are supported Sun computers with a minimum of Solaris 2.5 installed. See the [Openlink ODBC compatibility table](#) on page 29 for more information.
- Verify that the complete Solaris distribution, which provides the libraries and headers, and the SPARCCompiler is installed. The development environment on the Sun client must be Solaris 2.5 or later.
- Develop an application using the ODBC API.

Installing ODBC on the Solaris client

To install the OpenLink ODBC 4.2 software on the Solaris client:

1. Determine what client software will be installed for your CMS load. For more information, see [Determining the CMS version](#) on page 30 and the [Openlink ODBC compatibility table](#) on page 29.

ODBC installation

Note:

The following table provides some useful information for installing the ODBC software.

| CMS version | R3V6 or R3V8 | R3V9aj and later | R3V11af and later |
|---------------------|--------------|------------------|-------------------|
| Solaris OS version | 5.5.1 or 5.7 | 5.8 | 5.8 |
| ODBC client version | 2.5 or 2.6 | 2.8 | 2.8 |

2. Insert the CD-ROM, *Avaya CMS OPENLINK ODBC Driver* into the CD-ROM drive.

3. Log into the system as **root**.

4. Enter:

```
cd /usr
```

5. Enter:

```
ls
```

6. Verify that the server drivers are installed on the system. If the server drivers are installed, there will be an **openlink** directory.

7. Choose one of the following:

- If the server drivers are installed, continue with Step 8.
- If the server drivers are not installed, enter:

```
mkdir /usr/openlink
```

The system creates the **/usr/openlink** directory.

8. Enter:

```
cd openlink
```

Note:

If you are installing the client on the same system as the server, you must remove any existing ODBC taz files. Enter: **rm /usr/openlink/*taz**

9. Enter:

```
uname -a
```

The system displays the current Solaris version.

```
SunOS CMS1 5.8 Generic_108528-08 sun4u sparc SUNW,Ultra-5_10
```

10. Record the Solaris version for use later in this procedure.

Example:

In the previous example, the Solaris version is 5.8.

11. Choose one of the following commands to copy the client components to **/usr/openlink**:

- If Solaris version 5.5.1 or version 5.7 is installed, enter:

```
cp /cdrom/cdrom0/client/solaris2.5_2.6/* /usr/openlink
```

- If Solaris version 5.8 or later is installed, enter:

```
cp /cdrom/cdrom0/client/solaris2.8/* /usr/openlink
```

12. Enter:

```
./install.sh
```

Note:

If the required broker is running, you might see a message that asks you to shut down the broker. At the prompt, press **Enter** to choose the default.

The system displays the following message:

```
Extracting (srmi9zz.taz) ...
.....
.....
.....
Enter the port number the the broker will listen on for
client connections [Enter=Default] :
```

13. Accept the default setting by pressing **Enter**.

The system displays the following message:

```
Welcome to the OpenLink Admin Assistant Setup.

This program will install the HTTP based OpenLink Admin Assistant,
thereby enabling remote configuration for all OpenLink Server
Components (Rule Book,
Service and Database Agents) from any Web Browser.

TCP/IP Port to use? [ENTER=8000] :
```

14. Accept the default setting by pressing **Enter**.

The system displays the following message:

```
Log File? [ENTER=www_sv.log]
```

ODBC installation

15. Accept the default setting by pressing **Enter**.

The system displays the following message:

```
Log all requests (y/n)? [ENTER=n]
```

16. Accept the default setting by pressing **Enter**.

The system displays the following message:

```
Administrator account? [ENTER=admin]
```

17. Accept the default setting by pressing **Enter**.

The system displays the following message:

```
Administrator's password? [ENTER=admin]
```

18. Accept the default setting by pressing **Enter**.

The system displays the following message:

```
The OpenLink Admin Assistant is now ready for use.  
.....  
.....  
.....  
Enter the name of the user that will own the programs [ENTER=Use  
Current User Settings] :
```

19. Enter:

```
root
```

The system displays the following message.

```
Enter the name of the group that will own the programs [ENTER=Use  
Current Group Settings] :
```

20. Enter:

```
root
```

The system displays the following message:

```
Changing ownership ...  
  
End of installation
```

21. Go to [Configuring ODBC drivers on the Solaris client](#) on page 41.

Configuring ODBC drivers on the Solaris client

You must configure the correct drivers for your system to work properly and you must also modify the `/usr/openlink/cms_odbc.ini` file. You must place the modified `/usr/openlink/cms_odbc.ini` file in the `$HOME` directory as `.odbc.ini` for every user that will initiate the client application.

⚠ CAUTION:

The client application will fail if it is initiated by a user who does not have an `.odbc.ini` file.

To configure the ODBC 4.2 drivers on the Solaris client:

1. Enter:

```
cp /usr/openlink/cms_odbc.ini $HOME/.odbc.ini
```

The system copies the `cms_odbc.ini` file to the `$HOME/` directory and renames the `cms_odbc.ini` file to `.odbc.ini`

2. Enter:

```
cd $HOME
```

3. Open the `.odbc.ini` file. Enter:

```
vi .odbc.ini
```

4. Look for the appropriate Informix section in the file.

The following table provides some useful information about the ODBC software.

| CMS version | R3V6 or R3V8 | R3V9aj and later | R3V11af and later |
|---------------------------|--------------|------------------|-------------------|
| Informix server type | 7 | 2000 | 2000 |
| Solaris server OS version | 5.5.1 or 5.7 | 5.8 | 5.8 |

ODBC installation

5. Edit the `Host` parameter in the Informix section. Enter the host name of the system you will be connecting to.

Example:

If you use Informix 2000, the modified file will look similar to the following:

```
[Informix2000]
Driver = /usr/openlink/lib/oplodbc.so.1
Host    = CMS1
ServerType= Informix 2000
ServerOptions=
Database= cms
Options=
ReadOnly=Yes
FetchBufferSize= 60
```

6. Save and close the file by pressing **Esc**. Then enter:

```
:wq!
```

7. Edit your **.profile** file by entering:

```
vi .profile
```

8. Enter the following lines at the end of the **.profile** file:

```
LD_LIBRARY_PATH=$LD_LIBRARY_PATH:/usr/openlink/lib
export LD_LIBRARY_PATH
UDBCINI=$HOME/.odbc.ini
export UDBCINI
```

Example:

The modified **.profile** file should look similar to the following:

```
# PROFILEVERSION: r3v11af.x
# Warning: this file has been modified by CMS
# Be very careful when making changes.
# NOTE 1: do not remove the first line of the file
# NOTE 2: PROFILEVERSION indicates the load in which the
#         file is changed and delivered. Given that changes
#         to the file are not delivered every load,
#         the PROFILEVERSION does not generally equal
#         the load being built or installed. The PROFILEVERSION
#         should not be modified on a customer machine.
. . .
. . .
. . .
LD_LIBRARY_PATH=$LD_LIBRARY_PATH:/usr/openlink/lib
export LD_LIBRARY_PATH
UDBCINI=$HOME/.odbc.ini
export UDBCINI
```

9. Save and close the file by pressing **Esc**. Then enter:

```
:wq!
```

10. Enter:

```
. .profile
```

The system executes the **.profile** file.

11. Turn on the Openlink request broker by entering:

```
/cms/dc/odbc/odbc_init -r 1
```

12. Go to [Testing ODBC connectivity on a Solaris client](#) on page 44.

Testing ODBC connectivity on a Solaris client

On the Solaris client, initiate the test application to verify connectivity with the following procedure:

1. Enter:

- If the client and server software are on the same system, enter:

```
cd /usr/openlink/samples/ODBC
```

- If the client and server software are on different systems, enter:

```
cd /usr/openlink/odbcsdk/examples
```

2. Enter:

```
./odbctest
```

The system displays the following message:

```
DSN = InformixX; (the valid value for your CMS)
UID = Valid _UNIX_User_on_Server;
PWD = User_password
```

3. Enter the ODBC connect string:

Example:

```
DSN=Informix2000;UID=cms;PWD=cmspasswd
```

where DSN = data source name, UID = cms client ID, and PWD = cms client password.

4. At the SQL > prompt, enter a valid SQL query.

Example:

```
select count(*) from hsplrit
```

5. Enter:

```
exit
```

Note:

If an error occurs, the system displays an error message and the test application closes. For more information on what could have caused the error, see [Clients cannot connect to the ODBC server](#) on page 66 or [Possible failure causes for a test application error](#) on page 68.

Once the Solaris client software is installed and configured, you can start writing your application using the ODBC API.

About building an ODBC application on a Solaris client

The ODBC application is responsible for implementing the embedded ODBC code provided by the ODBC libraries linked to the driver manager for host/database connectivity, data access, and any other necessary processing. If the test connection is successful, the client has been properly configured.



Important:

Avaya cannot provide support for client-generated applications or other third-party software or related mapping.

Installing ODBC 4.2 on a Windows client

The OpenLink ODBC Request Agent software can be installed on your desktop computer or on your network for each client to access. Additional information on installing and configuring the ODBC driver can be found in the on-line Help file that is included on the CD-ROM, *Avaya CMS OPENLINK ODBC Driver*.

This section contains the following topics:

- [System requirements](#) on page 46
- [Installing the ODBC client on a Windows client](#) on page 46
- [Installing clients over the network](#) on page 48

System requirements

Before installing the OpenLink ODBC driver software on your computer, verify that:

- The client network software is installed.
Verify that you have a Winsock-compliant desktop TCP/IP product installed. Check for the existence of the **winsock.dll** file with Windows Explorer or through your file manager.
- Your computer is communicating with the CMS server over the network.
Use your desktop TCP/IP product's Packet Internet Groper (PING) utility to ensure that communication between your computer and the CMS server is functional. Do not proceed if basic communications between your computer and the server cannot be established.
- The desktop computer is running Microsoft Windows 98, Windows 2000, Windows NT 4.0, or Windows XP.

Installing the ODBC client on a Windows client

To install OpenLink ODBC client software on a Windows client:

1. Start Microsoft Windows.

Note:

The Windows XP interface is completely customizable. You may notice some differences based on your system configuration.

2. Insert the CD-ROM, *Avaya CMS OPENLINK ODBC Driver* into the CD-ROM drive.

3. Open Windows Explorer, and then select the CD-ROM drive with the ODBC CD-ROM disc.

4. Select the **Client** folder.

5. Select the **Win32** folder.

6. Double click the application, **SETUP.EXE**

The system displays the **Welcome** window.

Note:

Avaya recommends that you accept the default installation configuration.

7. Select **Next**.

The system displays the **Software License Agreement** window.

8. Select **Yes**.

The system displays the **Setup Type** window.

9. Select **Custom Client/Server Install**, and then select **Next**.

The system displays the **Choose Destination Location** window.

10. Select **Next**.

The system displays the **Select Components** window.

11. *Deselect* **JDBC Client**.

12. Select **Next**.

The system displays the **Select License File** window.

13. Select **Next**.

14. Go to the ODBC CD-ROM.

15. Select **client > Win32 > oplrqb.lic**

16. Select **Open**.

The system displays the **Select Program Folder** window.

Note:

If you are prompted to install the ODBC driver, select **Openlink Generic 32 Bit Driver v4.0**. If you will be connecting to systems using different versions of the ODBC software, verify that you do not delete the **Openlink Generic 32 Bit Driver**.

17. Select **Next**.

18. The system displays the **Start Copying Files** window.

19. Select **Next**.

The system installs the ODBC software and then displays the **Setup Complete** window.

20. Select **Finish**.
21. Go to [Configuring ODBC drivers on a Windows client](#) on page 49.

Installing clients over the network

To install ODBC on a desktop computer client that does not have a CD-ROM drive, or to install ODBC over the network:

1. Install the ODBC driver on a networked machine that has a CD-ROM drive. Use the appropriate procedure for the machine's operating system.
For more information, see [Installing ODBC 4.2 on a Windows client](#) on page 46.
2. Go to the system where you want to install the client.
3. Open the computer's Program Manager or Windows Explorer and go to the directory for the networked machine.
4. Copy the **OpenLink** folder from the networked machine.
5. Change directories to your client computer's hard drive.
6. Copy the **OpenLink** folder to your hard drive.
7. Run the application, **SETUP.EXE**.
8. Set up the software using the **Normal** option and the appropriate procedure for the machine's operating system.

For more information, see [Installing ODBC 4.2 on a Windows client](#) on page 46.

Configuring ODBC drivers on a Windows client

After the ODBC client software is installed, it must also be configured. Use the OpenLink ODBC Driver Administration utility to administer data sources for the clients.

This section contains the following topics:

- [Prerequisites](#) on page 49
- [Description of the ODBC Data Source Administrator window](#) on page 50
- [Description of the OpenLink ODBC Setup window](#) on page 51
- [Configuring an ODBC server data source](#) on page 53
- [Accessing the ODBC Data Source Administrator window](#) on page 55
- [Configuring a user data source](#) on page 56
- [Removing a data source](#) on page 57
- [Configuring ODBC tracing options](#) on page 57


Prerequisites

The following prerequisites must be met before configuring the client software:

- The server must have one of the following CMS loads installed:
 - R3V6
 - R3V8
 - R3V9aj or later
 - R3V11af or later
- The network communication software must be correctly installed and configured, and the network must be fully functional, so that the server and client can communicate.

Description of the ODBC Data Source Administrator window

The following figure shows the **ODBC Data Source Administrator** window on a Windows XP system. You will see some variation between different operating systems.




The following table describes the items in the **ODBC Data Source Administrator** window.

| Item | Description |
|-----------------------|--|
| Help button | This button accesses the ODBC on-line Help. |
| User DSN tab | This tab displays a page that contains options that allow you to add, delete, or configure data sources that are dedicated to a specific user's login ID. |
| System DSN tab | This tab allows you to add, delete, or configure data sources local to a computer, rather than dedicated to a user. |
| File DSN tab | This tab displays a page that provides options that allow you to add, delete, or configure file-based data sources. The file-based data sources are in a shared folder that is accessible by every client on the network. Avaya recommends that you do not add, delete, or configure file-based data sources for CMS. |
| Drivers tab | This tab displays a page that contains information about the types of drivers currently installed. |

| Item | Description |
|-------------------------------|---|
| Tracing tab | This tab displays a page that contains options that allow you to set up ODBC tracing. |
| Connection Pooling tab | This tab displays a page that contains options that will allow an application to reuse open connection handles. |
| About tab | This tab displays a page that contains information about ODBC. |
| Add button | This button allows you to add a new data source. |
| Remove button | This button allows you to remove an existing data source. |
| Configure button | This button allows you to configure an existing data source. |

Description of the OpenLink ODBC Setup window

The following figure shows the **OpenLink ODBC Setup** window on a Windows XP system. You will see some variation between different operating systems.



ODBC installation

The following table describes the items in the **OpenLink ODBC Setup** window.

| Field | Description |
|---|---|
| Datasource panel | |
| Name | In this field, enter a representative name for the server or database to which you are connecting to. For example, CMS - hostname. |
| Comment | In this field, enter a description of the data source to which you are connecting. For example, CMS ODBC 4.2. |
| Openlink Server panel | |
| Domain | In this field, enter the database type or user-defined logical representation of the underlying DBMS with which you are establishing an ODBC session. For example, Informix 2000. |
| Protocol | In this field, enter the network protocol you are using to access database data items. The default is TCP/IP. |
| Hostname | In this field, enter the network alias, or IP address, of the machine to which you want to make ODBC connections. |
| Port | In this field, enter the port number. The default is 5000. |
| Database panel | |
| Name | In this field, enter the ODBC data source names to specific database names for a provider type. For example, /cms. |
| Username | This is an optional entry field that contains a valid CMS user login ID for the database being represented by the provider type. |
| Optional Server (gateway configurations only) panel | |
| Server Name | This field can contain an optional entry for database connections after the database environment has been initialized. An entry is not required or recommended in this field. |

| Field | Description |
|------------------------------------|---|
| Others panel | |
| Read-only connection | This check box allows you to choose whether you do or do not want to enforce read-only database sessions for ODBC-compliant applications. This box should not be checked if you are accessing customer data. It should be checked if you are not accessing customer data. |
| No login dialog box | This check box allows you to choose whether you do or do not want to disable the pop-up login window during ODBC session establishment with a data source. |
| Defer fetching of long data | This check box allows you to choose whether you do or do not want to defer the fetching of long data. |
| Row buffer size | This is a variable-entry field that specifies the number of records to be transported over the network in a single network hop. This setting affects the performance of the OpenLink driver. The recommended setting for the CMS database is 60. |

Configuring an ODBC server data source

After associating the CMS data source with the OpenLink Generic 32 bit v4.0 driver, you must configure database access to a specific server.

Note:

The Windows XP interface is completely customizable. You may notice some differences based on your system configuration.

To configure your ODBC driver software to access CMS data:

1. Select **Start > Programs > Openlink Data Access Drivers > C++ Demo 32 Bit**
The system displays the **ODBC SDK 2.0 C++ Demo** window.
2. Select **Environment > Add Data Source**
The system displays the **Create New Data Source** window.
3. Select the **System Data Source (Applies to this machine only)** option.
4. Select **Next**.
The **Create New Data Source** window displays a list of data source drivers.
5. Select **Openlink Generic 32 Bit Driver v4.0**.

ODBC installation

6. Select **Next**.

The system displays your selections.

7. If the displayed selections are correct, select **Finish**.

The system displays the **Openlink ODBC Setup** window.

8. In the **Datasource** panel **Name:** field, enter a descriptive name for your data source.

Note:

In a multi-site call center situation, you can use this field to differentiate between call center locations.

9. In the **Datasource** panel **Comment:** field, you can optionally enter either:

- **Call Management System**

- Additional information related to the CMS data source

10. In the **Openlink Server** panel **Domain:** field, select one of the following options:

- If the data source is a CMS R3V6 or R3V8 system, select **Informix 7**
- If the data source is a CMS R3V9 or later system, select **Informix 2000**

Note:

For more information about your CMS load, see the [Openlink ODBC compatibility table](#) on page 29.

11. In the **Openlink Server** panel **Protocol:** field, enter:

TCP/IP

12. In the **Openlink Server** panel **Hostname:** field, enter the host name of the appropriate CMS system.

13. In the **Openlink Server** panel **Port:** field, enter the default port of your database host machine. The default is 5000.

14. In the **Database** panel **Name:** field, enter one of the following CMS paths:

- If the data source is a CMS R3V6 or R3V8 system, enter:

/cms/db/inf/cms

- If the data source is a CMS R3V9 or later system, enter:

cms

15. In the **Database** panel **Username:** field, you can optionally enter a valid CMS user login ID. If you enter a CMS user login ID, the system displays a default user name for each login to the data source.

16. Leave the **Optional Server** panel **Server Name:** field blank.

17. Verify that the following items in the **Others** panel are *not* selected:

- **Read-only connection**

If the check box is selected, complete access ODBC to customer-defined database tables (c_* tables) will be denied.

- **No login dialog box**

If the check box is selected, a login window will *not* be displayed when you connect to the CMS database.

Note:

You may select the **No login dialog box** check box to prevent the system from displaying a login window with each access to the database. Selecting this box is recommended only if the software you use to access the database, such as Crystal Reports, is password-enabled.

18. In the **Others** panel **Row Buffer Size:** field, enter a row buffer size of:

30

19. Choose one of the following steps:

- To accept the configuration, select the **OK** button.
- To cancel the configuration, select the **Cancel** button.

At this point, the ODBC driver software is installed on your computer.

20. Continue with [Configuring ODBC tracing options](#) on page 57 to specify additional configuration settings.

Note:

Once the driver is configured, the OpenLink ODBC driver is accessible to ODBC-enabled applications on your computer. Any queries that you send to the CMS database from client Windows applications, such as Microsoft Access, will use the ODBC feature to access data and copy it to your applications.

You need to format the data within your application. The data returned from your SQL queries is formatted in the manner described in [Database tables on page 71](#).

Accessing the ODBC Data Source Administrator window

The ODBC Driver Administration utility resides within your desktop environment's control panel. This utility is an optional method for adding and removing ODBC drivers. To access the ODBC Driver Administration utility after the OpenLink ODBC driver software has been installed, choose one of the following procedures, depending upon your version of Windows:

ODBC installation

- [Accessing the ODBC Data Source Administrator window with Windows 98, Windows 2000, or Windows NT 4.0](#) on page 56
- [Accessing the ODBC Data Source Administrator window with Windows XP](#) on page 56

Accessing the ODBC Data Source Administrator window with Windows 98, Windows 2000, or Windows NT 4.0

To access the ODBC Data Source Administrator window on a Windows 98, Windows 2000, or Windows NT 4.0 system:

1. In the Windows task bar, select **Start > Settings > Control Panel**.
The system displays the **Control Panel** window.
2. Double click **ODBC Data Sources**.
The system displays the **ODBC Data Source Administrator** window.
3. Select the **System DSN** tab, and then click **Add**.
4. Go to [Configuring an ODBC server data source](#) on page 53.

Accessing the ODBC Data Source Administrator window with Windows XP

To access the ODBC Data Source Administrator window on a Windows XP system:

Note:

The Windows XP interface is completely customizable. You may notice some differences based on your system configuration.

1. In the Windows task bar, select **Start > Control Panel**.
2. Select **Performance and Maintenance**.
3. Select **Administrative Tools**.
4. Double click **Data Sources (ODBC)**.
The system displays the **ODBC Data Source Administrator** window.
5. Select the **System DSN** tab, and then click **Add**.
6. Go to [Configuring an ODBC server data source](#) on page 53.

Configuring a user data source

Avaya strongly recommends that you administer system data sources as described in [Configuring an ODBC server data source](#) on page 53. It is not recommended that you administer data sources on a per-user login ID basis. However, this procedure is useful if you are providing access for a specific user.

To administer login ID-based data sources, complete the following steps:

1. In the **ODBC Data Source Administrator** window, select the **User DSN...** tab.
2. In the **ODBC Data Source Administrator** window, select the **Add...** button.

The system displays the **Create New Data Source** window.

3. Select the following driver:

OpenLink Generic 32 bit driver v4.0

4. Press the **Finish** or **OK** button.

The system displays the **OpenLink ODBC Setup** window.

5. Go to [Configuring an ODBC server data source](#) on page 53 and continue the procedure from Step 8 for data source setup procedures.

Removing a data source

To remove any data source, perform the following:

1. Select the appropriate ODBC data source.
2. Press the **Remove** button in the **ODBC Data Source** window and follow the prompts.

Configuring ODBC tracing options


You may specify how the ODBC driver traces ODBC function calls. If tracing is activated, the system generates a file that contains the actual ODBC function calls.

To set the ODBC tracing options:

1. In the **ODBC Data Source Administrator** window, select the **Tracing** tab.

Note:

For information on how to access the **ODBC Data Source Administrator** window, go to [Accessing the ODBC Data Source Administrator window](#) on page 55.



2. Choose one of the following options:

- a. To trace ODBC calls or observe ODBC activity, select the **Start Tracing Now** button.
- b. To stop tracing ODBC function calls automatically, select the **Stop Tracing Now** button. This will terminate the ODBC tracing upon completion of the ODBC session.
- c. To select or change the file to which the OpenLink Request Broker writes tracing information, either:
 - Enter a file name and path in the **Log file Path** field, or
 - Use the **Browse...** button to select the appropriate file from the **Select ODBC Log File** window.

Note:

The default log file is **SQL.LOG**.

⚠ CAUTION:

Do not change the default entry in the **Custom Trace DLL** field.

Viewing installed ODBC data source drivers

Use the **Drivers** window to verify installation of the OpenLink data source driver. For more information about what drivers should be installed on your system, go to the [Openlink ODBC compatibility table](#) on page 29. If the appropriate OpenLink data source driver is not displayed in the **Drivers** window, return to [Installing ODBC 4.2 on a Windows client](#) on page 46 and reinstall the driver.

To view a list of installed ODBC drivers:

1. In the **ODBC Data Source Administrator** window, select the **Drivers** tab.

Note:

For information on how to access the **ODBC Data Source Administrator** window, go to [Accessing the ODBC Data Source Administrator window](#) on page 55.

2. View detailed information about an installed driver by selecting the driver from the list, and then selecting the **About** tab.

The system displays the **About** page with the selected driver information.

Testing ODBC connectivity on a Windows client

After you have installed the OpenLink ODBC driver software on both the client and the server, you can open a demonstration connection to a data source on the server to show connectivity and test SQL access.

This section contains the following procedures:

- [Connecting to and accessing data](#) on page 60
- [Disconnecting from a data source](#) on page 63

Connecting to and accessing data


To connect to a data source from the client, complete the following steps:

Note:

The Windows XP interface is completely customizable. You may notice some differences based on your system configuration.


1. Go to the **Start** button and select **Programs > OpenLink Data Access Drivers > C++ Demo 32 bit**

The system displays the **ODBC SDK 2.0 C++ Demo** window.



2. Select **Environment > Open Connection**.

The system displays the **Select Data Source** window.



Note:

Depending on the ODBC driver version you are using, the **Select Data Source** window might display and you will be prompted to select a file or machine data source.


3. Select the **Machine Data Source** tab.

4. Select the data source that you want to use from the list, and then select **OK**.

Note:

You should have already configured the CMS data source. If you do not see a data source in the **SQL Data Sources** window, see [Configuring an ODBC server data source](#) on page 53.

The system displays the **OpenLink ODBC Login** window.



ODBC installation

Note:

The system will not display the **OpenLink ODBC Login** window if you selected the **No Login Dialog Box** option during the software configuration.


5. Enter your CMS server user name and password (CMS server login).

6. Select **Connect**.

The system displays the **ODBC SDK 2.0 C++ Demo** window for the connection.

7. Select **SQL > Execute SQL**.

The system displays the **ODBC SDK 2.0 C++ Demo** window.




8. Enter the following SQL query in the text box:

select count(*) from hsplit

Note:

Any valid SQL query may be entered.

Example:



9. Select **OK**.

The system displays the queried data in the **ODBC SDK 2.0 C++ Demo** window.

You should see a count column on the **ODBC SDK 2.0 C++ Demo** window. The value in this column is the number of records in the CMS `hsplit` table. This result confirms that you have successfully accessed the database from the client. Use this test as a troubleshooting tool in the future to verify connectivity and data access from the client.

Disconnecting from a data source

After you have completed test querying the database, you can disconnect from the data source through the ODBC driver software.

To disconnect from the data source:

1. Select **Environment > Close Connection**.

The system displays the **ODBC SDK 2.0 C++ Demo Close Current Connection** window.

2. Select **OK** to close the connection.

3. Select **File > Exit**

The system disconnects from the data source.

ODBC installation

Troubleshooting

This section presents general troubleshooting procedures and error messages for ODBC. For more detailed information, see the on-line Help file that is included on the Avaya CMS OPENLINK ODBC driver CD-ROM.

 **Important:**

If you choose to develop an application for the ODBC driver, Avaya cannot provide support for that application or for any other third-party software or related mapping.

This section contains the following topics:

- [Clients cannot connect to the ODBC server](#) on page 66
- [Multiple connections with the same username](#) on page 66
- [Network support](#) on page 67
- [Server log file](#) on page 67
- [Client trace](#) on page 67
- [Possible failure causes for a test application error](#) on page 68
- [OpenLink error messages](#) on page 69

Clients cannot connect to the ODBC server

Verify that the ODBC Request Broker is active on the server by entering:

```
ps -ef | grep oplrqb
```

One of the displayed messages should show the oplrqb process running from the **/usr/openlink/bin** directory.

- If CMS R3V9 or later is installed, the system displays a message similar to the following:

```
root 1462 1459 0 14:41:38 ?
0:00 /usr/openlink/bin/oplrqb -f +configfile /cms/dc/odbc/
cmsrqb4.2_init +loglevel 5 +l
```

- If CMS R3V6 or CMS R3V8 is installed, the system displays a message similar to the following:

```
root 1462 1459 0 14:41:38 ?
0:00 /usr/openlink/bin/oplrqb -f +configfile /cms/dc/odbc/
cmsrqb3.2_init +loglevel 5 +l
```

Multiple connections with the same username

To make multiple connections with the same username:

1. Modify the **cmsrqb4.2_init** file under **/cms/dc/odbc** so that the **ReUse** field under **[generic_inf2000]** is set to **never**.

Note:

The default setting is `ifsame database,ifsame user`.

2. Enter:

```
cd /cms/dc/odbc
```

3. Turn off ODBC by entering:

```
./odbc_init -r 0
```

4. Turn on ODBC by entering:

```
./odbc_init -r 1
```

Network support

Avaya does not control customer network configuration or ODBC-enabled client applications. Installation and ongoing maintenance support is limited to determining if data is being transferred correctly in the most basic client/server relationship. This is defined as a CMS system running ODBC on the same network hub as the client PC.

Verify that the trouble occurs on the same network subnet. Then continue with troubleshooting procedures. If the trouble does not occur on the same network subnet, contact the Avaya help line.

Server log file

Once the ODBC driver is installed and initiated, the server log file, **odbc.log** records the logging levels of all ODBC activities. The default log level is **5**. Avaya recommends that users do not set the log level to a value greater than 5. See [Using the server utilities](#) on page 35 for more information.

Review the **odbc.log** file for information about ODBC sessions. Archived records of past ODBC sessions are maintained in the **odbc.log.01** and **odbc.log.02** files. These logging levels are set by running `./odbc_init -1` located in the `/cms/dc/odbc` directory. For more information, see [Setting log levels](#) on page 35.

Client trace

The OpenLink client component configuration utility, located in the OpenLink group on your Windows desktop, allows you to enable or disable ODBC trace logging. Trace logging provides you with:

- Records of your entire ODBC session, including all ODBC calls made by the ODBC-compliant application you are using
- Native database error messages that might not have been replaced by the ODBC-compliant application you were using.

See [Configuring ODBC tracing options](#) on page 57 for information on configuring this utility.

Possible failure causes for a test application error

A test application error could result from one of the following causes:

| Problem | Solution |
|--|--|
| The driver is not active on the CMS server. | Verify that the ODBC driver is active on the server by entering: <code>ps -ef grep oplrqb</code> You should see an <code>oplrqb</code> process running. |
| The <code>.odbc.ini</code> file is not in the initiator's <code>\$HOME</code> directory. | Place the <code>.odbc.ini</code> file in the initiator's <code>\$HOME</code> directory. |
| The <code>.odbc.ini</code> file is incorrect. | Verify that the entered host is correct and the database path is correct. For example, <code>cms</code> . |
| The <code>LD_LIBRARY_PATH</code> is not set. | Enter <code>echo \$LD_LIBRARY_PATH</code> to verify that <code>LD_LIBRARY_PATH</code> is included in the display. See Testing ODBC connectivity on a Solaris client on page 44 for more information. |
| The <code>UDBCINI</code> is not set. | Enter <code>echo \$UDBCINI</code> to verify that <code>\$HOME/.odbc.ini</code> is included in the display. See Configuring ODBC drivers on the Solaris client on page 41 for more information. |
| The data source is not consistent with the <code>cmsrqb4.2_init</code> entry. | Verify that the data source you entered is correct. For example, <code>Informix2000</code> . |

For more information about configuration settings, see the [Openlink ODBC compatibility table](#) on page 29.

OpenLink error messages

The error messages that you might receive from the OpenLink ODBC driver are displayed on the client and in the server log file. Some common error messages that you might receive and possible solutions are shown in the following table.

| Message | Possible solution |
|--|---|
| Invalid Username/ Password | <p>This message is displayed when:</p> <ul style="list-style-type: none"> ● The operating system-level username and password verification is in use, and ● When you enter an invalid operating system-level username and password combination when connecting to your OpenLink ODBC Data Source. <p>This occurs even when the username and password combination entered is valid at the database level.</p> |
| Unable to Locate Requested Service | <p>This message is displayed as a result of the OpenLink Session Rules Book being incorrectly configured. This error can be caused by an invalid reference to the OpenLink database agent executable program responsible for providing database access. This error will not occur with the default settings.</p> |
| Unable to Load OpenLink Request Agent | <p>This message indicates a client machine problem at the network transport level. Verify that your client machine's network software is correctly configured.</p> |
| Remote Procedure Call (RPC) Unable to Send | <p>This message indicates a corruption of the communications channel being used by the OpenLink Request Agent. This error typically occurs when the server Request Broker has been shut down. Verify the status of the Request Broker. Try to re-initiate the ODBC session.</p> |
| RPC Timed Out | <p>This message is displayed when timeout settings in either the client side or server side Session Rules Books have been exceeded. This message typically occurs when communication cannot be established from client to server or server to client. Verify that the oplrqb is running on the server side by entering: <code>ps -ef grep oplrqb</code> You should see an oplrqb process running.</p> |

Troubleshooting

| | |
|--|---|
| RPC Unable to Receive | <p>This message indicates that the server Request Broker is no longer communicating with the client.</p> <p>This error occurs when the server Request Broker has been shut down or re-initiated during a session. Verify that the Request Broker is active on the server.</p> |
| RPC Host Unknown | <p>This message results from a network failure or invalid host entry in the Data Source Setup window.</p> <p>Check the Hostname: field entry in that window; if you suspect a network problem, verify this and correct it if necessary; or retry your ODBC session.</p> |
| Unknown Database Agent Requested | <p>This message results when the client administration associated with the ODBC session does not resolve to the oplrqb rules in cmsrqb4.2_init.</p> <p>To resolve this error, the Data Source Setup window Type: field should be set to the appropriate Informix provider type or domain name. For more information see Openlink ODBC compatibility table on page 29. Retry your ODBC session.</p> |
| Unable to Start the Requested Database Agent | <p>This message results when the oplrqb is able to resolve to a database agent, but is unable to execute the program.</p> <p>To resolve this, set the Type: field on the Data Source Setup window to the appropriate Informix provider type or domain name. For more information see Openlink ODBC compatibility table on page 29.</p> <p>Alternately, set the generic_inf9 to inf9_mv. Finally, the inf9_mv should exist in /usr/openlink/bin as an executable.</p> |
| Database Errors | <p>Database errors are displayed after failed database accesses.</p> <p>To resolve this problem, correct the database query and resubmit it.</p> |



Database tables

This section describes the CMS historical database tables that can be accessed through ODBC. For detailed information about specific database tables, see the appropriate database items and calculations document for your CMS release.

This section includes the following topics:

- [Things to consider when using ODBC](#) on page 71
- [CMS database logic structure](#) on page 72
- [CMS database table names](#) on page 73
- [Description of the CMS database tables](#) on page 76
- [CMS database table items](#) on page 79
- [Generating a CMS database schema](#) on page 138

Things to consider when using ODBC

Some things to consider when using ODBC with CMS are:

Dictionary names - Clients can access CMS Dictionary names. You must map the synonym to the report from the client.

Permissions - Applications that access Informix externally, such as database access scripts, may not work if the table permission script tries to access a table to which permission is denied.

Field display - The time and date data you receive from the database may not be formatted. Generally, times may be shown in seconds or in 24-hour (military) format. You will need to review data for formatting when you import it into your software application. The data returned from your SQL queries will be formatted in the manner described in your database interface specifications. See your software's documentation for further information on formatting data.

Switch features and capabilities - Some switch features and capabilities have an impact on CMS open database items. For more information on these features and capabilities, see the appropriate database items and calculations document for your CMS release.

CMS database logic structure

CMS historical tables store information in one record per row format. This formatting affects the way data can be accessed through ODBC. When accessing data in the historical tables, you may need to sum the information to retrieve complete data.

For example, a record will be created for each split/skill that an agent is logged into in the agent tables. If an agent is logged into four splits/skills, there will be four records for that agent. Similarly, if an agent starts the day with four splits/skills, and is added to a fifth split/skill before the end of the day, the agent's fifth record will be generated only from the point at which the additional split/skill was added. The other four records will reflect the total logon time.

This section contains the following topics:

- [Agent tables](#) on page 72
- [VDN tables](#) on page 72
- [Circular structure tables](#) on page 73

Agent tables

If an agent logs off and logs on more than once in a specified interval, another complete set of records is created for that agent for each logon in the agent tables.

For example, if an agent logs into four split/skills, logs out, and then logs back on during a set interval, there will be two sets of four records for that agent, one set per logon.

VDN tables

The VDN tables store one record per vector on which a VDN terminates. Therefore, if the terminating vector for a specific VDN changes in a set interval, there are two records for that VDN - one per terminating vector. This logic also applies to the Vector, Trunk, Trunk Group, and Split/Skill tables. If information is required from these tables, a sum structured query language (SQL) query may be necessary to access complete data from each table.

Circular structure tables

The Exceptions, Call Record, and Agent Trace tables are circular files. These tables populate continuously, until the table capacity plus ten percent has been reached. At that point, the oldest ten percent of the records are deleted.

For example, if an agent trace table has a capacity of 100 rows, and the total rows populated equals 110, the oldest ten rows will automatically be deleted. Therefore, the data in that table will change continuously as the table is updated.

CMS database table names

To select data for external use, you must use the names listed in the following table in your queries. The following table contains all the tables that are ODBC-accessible in CMS and a brief description of the data in each. If a table is not listed here, it is not accessible through ODBC. The table will still be accessible by **root**. All tables included in this chapter have read-only external user access.

ODBC accessible tables

| Name | Data stored |
|---------------|--|
| hsplit | Split/Skill data for each intrahour interval |
| dsplit | Split/Skill data summarized by day |
| wsplit | Split/Skill data summarized by week |
| msplit | Split/Skill data summarized by month |
| hagent | Agent data for each intrahour interval |
| dagent | Agent data summarized by day |
| wagent | Agent data summarized by week |
| magent | Agent data summarized by month |
| htkgrp | Trunk group data for each intrahour interval |
| dtkgrp | Trunk group data summarized by day |

ODBC accessible tables (Continued)

| Name | Data stored |
|-----------------|---|
| wtkgrp | Trunk group data summarized by week |
| mtkgrp | Trunk group data summarized by month |
| htrunk | Trunk data for intrahour interval |
| dtrunk | Trunk data summarized by day |
| wtrunk | Trunk data summarized by week |
| mtrunk | Trunk data summarized by month |
| hvector | Vector data for each intrahour interval |
| dvector | Vector data summarized by day |
| wvector | Vector data summarized by week |
| mvector | Vector data summarized by month |
| hvdn | VDN data for each intrahour interval |
| dvdn | VDN data summarized by day |
| wvdn | VDN data summarized by week |
| mvdn | VDN data summarized by month |
| hcwc | Call work code data for each intrahour interval |
| dcwc | Call work code data summarized by day |
| wcwc | Call work code data summarized by week |
| mcwc | Call work code data summarized by month |
| call_rec | Call record data |
| d_secs | The number of seconds in the daily data collection period |
| m_secs | The number of seconds in the monthly data collection period |
| w_secs | The number of seconds in the weekly data collection period |

ODBC accessible tables (Continued)

| Name | Data stored |
|---------------------|--|
| arch_stat | The status of archiver executions |
| customer_log | The customer error log data |
| agroups | Agent group definitions |
| synonyms | Dictionary synonyms |
| acd_shifts | Shift times and maximum agents logged in for each shift |
| dbitems | Dictionary standard and custom database items, constants, and calculations |
| f_cday | Forecast current day configuration data by split/skill |
| f_cdayrep | Current day forecast data by split/skill |
| haglog | Agent login and logout information |
| ag_actv | Agent activity trace data |
| agex | Agent exceptions |
| fullex | Disk full exceptions |
| spex | Split/skill exceptions |
| tgex | Trunk group exceptions |
| vecex | Vector exceptions |
| vdnex | VDN exceptions |
| linkex | Link down exceptions |
| mctex | Malicious call trace exceptions |

Description of the CMS database tables

This section provides an overview of the types of data collected by CMS and definitions for the data presented in [CMS database table items](#) on page 79.

This section contains the following information:

- [About the Database item column](#) on page 76
- [About the Data types column](#) on page 77
- [About the Column type and Length columns](#) on page 77

About the Database item column

The Database item column contains the name of a particular database item. Many database items are contained in more than one database table.

Index database items

The index database items in each table are marked (index). Indexes add structure to table rows so that CMS can retrieve data faster. The row search criteria you define for custom reports should be based on indexes whenever possible. For historical custom reports, always include a "where" clause based on the ROW_DATE database item.

Call-based data and interval-based data

Items in the CMS database can be either call-based or interval-based. Most CMS database items are call-based. Call-based data is committed to the database after a call completes. Therefore, if a call starts and ends in different collection intervals, all of the data are recorded in the interval in which the call and any After Call Work (ACW) are completed.

Interval-based data represents the amount of time during a collection interval that is used for a particular activity. Interval-based items are updated throughout the collection interval and timing is restarted at the end of the interval. Most interval-based items start with I_ or TI_. The database items ALLINUSETIME (trunk-group tables) and MBUSYTIME (trunk and trunk-group tables) are also interval-based. Each database item has a defined column type.

About the Data types column

The Data type column contains a letter that represents a specific data type. The following table describes the data types:

| Data type | Description |
|---------------------------------|---|
| A = Administrative data | Administered on the ECS or on CMS. For example, the database item INTRVL in the split/skill table contains the number of minutes in the intrahour interval (15, 30, 60) assigned for the specified ACD on CMS. |
| B = Busy Hour data | Gives data that is only meaningful for the busy hour. |
| C = Cumulative data | Accumulates throughout the collection interval. Most real-time database items contain cumulative data. |
| I = Row Identifier data | Gives data that is common to all tables, such as time, date, split in the split/skill tables, and so on. |
| M = Maximum Interval Value data | Gives data that is the maximum reached for any value in the specified interval. |
| N = Special Table data | Belongs only to a specific table, such as the Historical Agent Login/Logout table or Current Day Forecast table. |
| S = Status data | Shows the current status (a snapshot of a particular ACD element). For example, the database item INQUEUE in the split/skill real-time table contains the number of split/skill calls currently waiting in queue. |

Note:

Administrative, Cumulative, Maximum Interval Value, Row Identifier and Busy Hour data items apply to historical and real-time database items.

Special Table data items apply only to historical database items.

About the Column type and Length columns

The Column type and Length columns describe the format of a database item. These columns include either the length in bits of the database item or the Informix data type.

Column type and length information is included for the user's reference. Because data gathered through ODBC can be used in a variety of applications, it is helpful to know what type of data you are accessing and how long it is in bytes. Any difference or exception in the column type or length between tables in a table group is indicated in the Column type and Length columns.

Informix data column types table

The following table defines the data column types.

| Column type | Definition |
|------------------|--|
| char(<i>n</i>) | An ASCII string of <i>n</i> characters, 1 byte per character. |
| date | Informix date type, 4 bytes long. The Informix date format is yyyy-mm-dd. For example, May 19, 1998 would display as: 1998-05-19. |
| integer | 4 byte integer |
| smallint | 2 byte integer |
| smallfloat | Informix floating point numerical type, 4 bytes long. The Informix smallfloat format is a decimal type used for percentages, and includes a comma and a plus/minus sign. |

CMS database table items

This section provides a list of the database items that can be accessed through ODBC. Not all database items will be available with every CMS or switch release.

For additional information about specific database items, see the appropriate database items and calculations document for your CMS release. Descriptions are provided for any items that are not included in the database items and calculations document.

This section contains the following topics:

- [Agent database items](#) on page 79
- [Agent Login/Logout database items](#) on page 90
- [Agent Trace database items](#) on page 91
- [Call Record database items](#) on page 94
- [Call Work Codes database items](#) on page 96
- [Exceptions historical database items](#) on page 97
- [Split/Skill database items](#) on page 103
- [Trunk Group database items](#) on page 111
- [Trunk database items](#) on page 116
- [Vector database items](#) on page 119
- [VDN database items](#) on page 122
- [Forecasting database tables](#) on page 129
- [Administrative database tables](#) on page 131

Agent database items

The Agent database item descriptions apply only to historical items. Historical agent database items apply to the Intrahour Agent (**hagent**), Daily Agent (**dagent**), Weekly

Database tables

Agent (**wagent**), and Monthly Agent (**magent**) tables. Unless indicated otherwise, all items listed in the [Agent database item table](#) on page 80 are included in all four tables.

Agent database item table

| Database item | Data type | Column type | Length |
|----------------|-----------|--|---------|
| ABNCALLS | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| ABNTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| ACD (index) | I | smallint | 2 bytes |
| ACD_RELEASE | C | integer (<i>not</i> in hagent table) | 4 bytes |
| ACDAUXOUTCALLS | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| ACDCALLS | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| ACDCALLS_R1 | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| ACDCALLS_R2 | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| ACDTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |

Agent database item table (Continued)

| Database item | Data type | Column type | Length |
|----------------|-----------|------------------------------|---------|
| ACWINCALLS | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| ACWINTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| ACWOUTADJCALLS | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| ACWOUTCALLS | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| ACWOUTOFFCALLS | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| ACWOUTOFFTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| ACWOUTTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| ACWTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| ANSRINGTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |

Database tables

Agent database item table (Continued)

| Database item | Data type | Column type | Length |
|----------------|-----------|------------------------------|---------|
| ASSISTS | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| AUXINCALLS | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| AUXINTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| AUXOUTADJCALLS | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| AUXOUTCALLS | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| AUXOUTOFFCALLS | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| AUXOUTOFFTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| AUXOUTTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |

Agent database item table (Continued)

| Database item | Data type | Column type | Length |
|-----------------|-----------|------------------------------|---------|
| CONFERENCE | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| DA_ABNCALLS | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| DA_ABNTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| DA_ACDCALLS | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| DA_ACDTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| DA_ACWINCALLS | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| DA_ACWINTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| DA_ACWOADJCALLS | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |

Database tables

Agent database item table (Continued)

| Database item | Data type | Column type | Length |
|-----------------|-----------|------------------------------|---------|
| DA_ACWOCALLS | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| DA_ACWOFFFCALLS | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| DA_ACWOFFFTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| DA_ACWOTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| DA_ACWTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| DA_ANSTIME | C | integer | 4 bytes |
| | | smallint (hagent table) | 2 bytes |
| DA_OTHERCALLS | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| DA_OTHERTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| DA_RELEASE | C | integer | 4 bytes |

Agent database item table (Continued)

| Database item | Data type | Column type | Length |
|------------------|-----------|------------------------------|-----------------------------------|
| EVENT1-9 | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| EXTENSION | A | char(6) | 6 byte ASCII text string |
| HOLDABNCALLS | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| HOLDACDTIME | C | integer | 4 bytes |
| HOLDCALLS | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| HOLDTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| I_ACDAUXINTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| I_ACDAUX_OUTTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| I_ACDOOTHERTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| I_ACDDTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |

Database tables

Agent database item table (Continued)

| Database item | Data type | Column type | Length |
|--|-----------|-------------------|---------|
| I_ACWINTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| I_ACWOUTTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| I_ACWTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| I_AUXINTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| I_AUXOUTTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| I_AUXSTBYTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| I_AUXTIME | C | integer | 4 bytes |
| I_AUXTIME0 - 99 (I_AUXTIME0 - 99 is only available with a CMS load that has been upgraded to use 100 AUX reason codes.) | C | integer | 4 bytes |
| I_AUXTIME_R1 | C | integer | 4 bytes |
| I_AUXTIME_R2 | C | integer | 4 bytes |
| I_AVAILTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |

Agent database item table (Continued)

| Database item | Data type | Column type | Length |
|--------------------|-----------|---------------------------------|---------|
| I_DA_ACDTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| I_DA_ACWTIME | C | integer | 4 bytes |
| | | smallint (hagent table) | 2 bytes |
| I_OTHERSTBYTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| I_OTHERSTBYTIME_R1 | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| I_OTHERSTBYTIME_R2 | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| I_OTHERTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| I_RINGTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| I_STAFFTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| INCOMPLETE | C | smallint | 2 bytes |
| INTRVL | A | smallint (only in hagent table) | 2 bytes |
| LOC_ID | C | integer | 4 bytes |

Database tables

Agent database item table (Continued)

| Database item | Data type | Column type | Length |
|---------------------|-----------|------------------------------|------------------------------------|
| LOGID (index) | A | char(10) | 10 byte ASCII text string |
| NOANSREDIR | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| O_ACDCALLS | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| O_ACDTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| O_ACWTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| PHANTOMABNS | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| RINGCALLS | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |
| RINGTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| ROW_DATE (index) | I | date | 4 byte Informi x date |

Agent database item table (Continued)

| Database item | Data type | Column type | Length |
|---|-----------|---------------------------------------|---------|
| SPLIT (index) | I | smallint | 2 bytes |
| STARTTIME | I | smallint (only in hagent table) | 2 bytes |
| TI_AUXTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| TI_AUXTIME0 - 9 or TI_AUXTIME0 - 99 (TI_AUXTIME0 - 99 is only available with a CMS load that has been upgraded to use 100 AUX reason codes.) | C | integer | 4 bytes |
| TI_AVAILTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| TI_OTHERTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| TI_STAFFTIME | C | integer | 4 bytes |
| | | smallint (hagent) | 2 bytes |
| TRANSFERRED | C | smallint (dagent, hagent) | 2 bytes |
| | | integer (magent, wagent) | 4 bytes |

Agent Login/Logout database items

The Agent Login/Logout database items are historical items that apply to the Agent Login/Logout (**haglog**) table. The [Agent Login/Logout database item table](#) on page 90 describes the data items in the CMS Agent Login/Logout database.

Agent Login/Logout database item table

| Database item | Column type | Length |
|----------------|-------------|------------------------------------|
| ACD (index) | smallint | 2 bytes |
| EXTN | char(6) | 6 byte ASCII text string |
| INFLAG | char(1) | 1 byte ASCII text string |
| LOC_ID | integer | 4 bytes |
| LOGID | char(10) | 10 byte ASCII text string |
| LOGIN | integer | 4 bytes |
| LOGONSKILL2-20 | smallint | 2 bytes |
| LOGOUT | integer | 4 bytes |
| LOGOUT_DATE | date | 4 byte Informix date |
| LOGOUT_REASON | smallint | 2 bytes |
| OUTFLAG | char(1) | 1 byte ASCII text string |
| PREFERENCE | integer | 4 bytes |
| SKLEVEL | integer | 4 bytes |
| SKLEVEL2-20 | integer | 4 bytes |
| SKPERCENT | integer | 4 bytes |

Agent Login/Logout database item table (Continued)

| Database item | Column type | Length |
|---------------------|-------------|-----------------------------------|
| SKPERCENT2-20 | integer | 4 bytes |
| ROW_DATE (index) | date | 4 byte Informix date |
| SKILLTYPE | char(1) | 1 byte ASCII text string |
| SKILLTYPE2-4 | char(1) | 1 byte ASCII text string |
| SKLEVEL | smallint | 2 bytes |
| SKLEVEL2-20 | smallint | 2 bytes |
| SPLIT (index) | smallint | 2 bytes |

Agent Trace database items

The Agent Trace database item descriptions are historical items that apply specifically to the Agent Trace (**ag_actv**) table. The [Agent Trace database item table](#) on page 91 describes the data items in the CMS Agent Trace database.

Agent Trace database item table

| Database item | Column type | Length |
|----------------|-------------|-----------------------------------|
| ACD (index) | smallint | 2 bytes |
| AGT_RELEASED | char(1) | 1 byte ASCII text string |
| ASSIST_ACTV | char(1) | 1 byte ASCII text string |

Agent Trace database item table (Continued)

| Database item | Column type | Length |
|------------------|-------------|------------------------------------|
| AUXREASON | smallint | 2 bytes |
| CALLER_HOLD | char(1) | 1 byte ASCII text string |
| CALLING_II | char(2) | 2 byte ASCII text string |
| CALLING_PTY | char(12) | 12 byte ASCII text string |
| CONFERENCE | char(1) | 1 byte ASCII text string |
| DIGITS_DIALED | char(16) | 16 byte ASCII text string |
| DIRECTION | smallint | 2 bytes |
| DURATION | integer | 4 bytes |
| EVENT_TIME | integer | 4 bytes |
| EXT_CALL_ORIG | char(1) | 1 byte ASCII text string |
| KEYBD_DIALED | char(1) | 1 byte ASCII text string |
| LOC_ID | integer | 4 bytes |
| LOGID (index) | char(10) | 10 byte ASCII text string |
| LOGOUTREASON | smallint | 2 bytes |

Agent Trace database item table (Continued)

| Database item | Column type | Length |
|---------------------|-------------|------------------------------------|
| MCT | char(1) | 1 byte ASCII text string |
| RECONNECT | char(1) | 1 byte ASCII text string |
| ROW_DATE (index) | date | 4 byte Informix date |
| SPLIT | smallint | 2 bytes |
| STARTTIME | smallint | 2 bytes |
| TRANSFERRED | char(1) | 1 byte ASCII text string |
| UCID | char(20) | 20 byte ASCII text string |
| WMODE_SEQ | smallint | 2 bytes |
| WORKCODE | char(16) | 16 byte ASCII text string |
| WORKMODE | smallint | 2 bytes |

Call Record database items

The Call Record database item descriptions are historical items that apply specifically to the Call Record (**call_rec**) table. The [Call Record database item table](#) on page 94 describes the database items in the CMS Call Record database.

Call Record database item table

| Database item | Column type | Length |
|----------------|-------------|------------------------------------|
| ACD (index) | smallint | 2 bytes |
| ACWTIME | integer | 4 bytes |
| AGT_RELEASED | smallint | 2 bytes |
| ANSHOLDTIME | integer | 4 bytes |
| ANSLOGIN | char(9) | 9 byte ASCII text string |
| ANSREASON | smallint | 2 bytes |
| ASSIST | smallint | 2 bytes |
| AUDIO | smallint | 2 bytes |
| CALLID | integer | 4 bytes |
| CALLING_II | char(2) | 2 byte ASCII text string |
| CALLING_PTY | char(12) | 12 byte ASCII string |
| CONFERENCE | smallint | 2 bytes |
| CONSULTTIME | integer | 4 bytes |
| DA_QUEUED | smallint | 2 bytes |
| DIALED_NUM | char(24) | 24 byte ASCII text string |
| DISPIVECTOR | smallint | 2 bytes |

Call Record database item table (Continued)

| Database item | Column type | Length |
|---------------|-------------|------------------------------------|
| DISPOSITION | smallint | 2 bytes |
| DISPPRIORITY | smallint | 2 bytes |
| DISPSKLEVEL | smallint | 2 bytes |
| DISPSPLIT | smallint | 2 bytes |
| DISPTIME | integer | 4 bytes |
| DISPVDN | char(5) | 5 byte ASCII text string |
| DURATION | integer | 4 bytes |
| EQLOC | char(8) | 8 byte ASCII text string |
| EVENT1-9 | smallint | 2 bytes |
| FIRSTVECTOR | smallint | 2 bytes |
| FIRSTVDN | char(5) | 5 byte ASCII text string |
| HELD | smallint | 2 bytes |
| HOLDABN | smallint | 2 bytes |
| LASTCWC | char(16) | 16 byte ASCII text string |
| LASTDIGITS | char(16) | 16 byte ASCII text string |
| LASTOBSERVER | char(9) | 9 byte ASCII text string |
| MALICIOUS | smallint | 2 bytes |

Call Record database item table (Continued)

| Database item | Column type | Length |
|---------------|-------------|------------------------------------|
| NETINTIME | integer | 4 bytes |
| OBSERVINGCALL | smallint | 2 bytes |
| ORIGHOLDTIME | integer | 4 bytes |
| ORIGLOGIN | char(9) | 9 byte ASCII text string |
| ORIGREASON | smallint | 2 bytes |
| ROW_DATE | date | 4 byte Informix date |
| ROW_TIME | smallint | 2 bytes |
| SEGMENT | smallint | 2 bytes |
| SEGSTART | integer | 4 bytes |
| SEGSTOP | integer | 4 bytes |
| SPLIT1 | smallint | 2 bytes |
| SPLIT2 | smallint | 2 bytes |
| SPLIT3 | smallint | 2 bytes |
| TALKTIME | integer | 4 bytes |
| TKGRP | smallint | 2 bytes |
| TRANSFERRED | smallint | 2 bytes |
| UCID | char(20) | 20-byte ASCII text string |

Call Work Codes database items

The Call Work Codes database item descriptions apply to historical items. Historical call work codes database items apply to the Intrahour Call Work Codes (**hcwc**), Daily Call Work Codes (**dcwc**), Weekly Call Work Codes (**wcwc**), and Monthly Call Work Codes

(**mcwc**) tables. Unless indicated otherwise, all items listed in the [Call Work Codes database item table](#) on page 97 are included in all four tables.

Call Work Codes database item table

| Database item | Data type | Column type | Length |
|---------------------|-----------|-------------------------|------------------------------------|
| ACD (index) | I | smallint | 2 bytes |
| ACDCALLS | C | integer | 4 bytes |
| | | smallint (hcwc) | 2 bytes |
| ACDTIME | C | integer | 4 bytes |
| ACWTIME | C | integer | 4 bytes |
| CWC (index) | I | char(16) | 16 byte ASCII text string |
| INCOMPLETE | C | smallint | 2 bytes |
| INTRVL | A | smallint (hcwc only) | 2 bytes |
| ROW_DATE (index) | I | date | 4 byte Informix date |
| STARTTIME | I | smallint (hcwc) | 2 bytes |

Exceptions historical database items

CMS stores exception types using the numerical values, then translates the numbers into the text you see in standard exception reports. For detailed information about specific database items, see *Avaya CMS Database Items and Calculations*, 585-780-702.

This section contains the following exception tables:

- [Agent Exceptions database items](#) on page 98
- [Split/Skill Exceptions database items](#) on page 99
- [Trunk Group Exceptions database items](#) on page 99

Database tables

- [VDN Exceptions database items](#) on page 100
- [Vector Exceptions database items](#) on page 101
- [Malicious Call Trace Exceptions database items](#) on page 101
- [Data Collection Exceptions database items](#) on page 102
- [Disk Full Exceptions database items](#) on page 103

Agent Exceptions database items

The Agent Exceptions database items apply to the Agent Exceptions (**agex**) table.

Agent Exceptions database item table

| Database item | Column type | Length |
|---------------------|-------------|------------------------------------|
| ACD | smallint | 2 bytes |
| EXTYPE | smallint | 2 bytes |
| LOGID | char(10) | 10 byte ASCII text string |
| REASON_CODE | smallint | 2 bytes |
| ROW_DATE (index) | date | 4 byte Informix date |
| ROW_TIME | smallint | 2 bytes |
| SEQNO | integer | 4 bytes |
| SPLIT | smallint | 2 bytes |
| THRESHOLD | smallint | 2 bytes |
| TIME | smallint | 2 bytes |
| AGLOCID | smallint | 2 bytes |

Split/Skill Exceptions database items

The Split/Skill Exceptions database items apply to the Split/Skill Exceptions (**spex**) table.

Split/Skill Exceptions database item table

| Database item | Column type | Length |
|---------------------|-------------|----------------------------|
| ACD | smallint | 2 bytes |
| EXTYPE | smallint | 2 bytes |
| ROW_DATE (index) | date | 4 byte Informix date |
| ROW_TIME | smallint | 2 bytes |
| SEQNO | integer | 4 bytes |
| SPLIT | smallint | 2 bytes |
| THRESHOLD | smallint | 2 bytes |
| TIME | smallint | 2 bytes |

Trunk Group Exceptions database items

The Trunk Group Exceptions database items apply to the Trunk Group Exceptions (**tgex**) table.

Trunk Group Exceptions database item table

| Database item | Column type | Length |
|----------------|-------------|------------------------------------|
| ACD (index) | smallint | 2 bytes |
| EXTYPE | smallint | 2 bytes |
| EQLOC | char(9) | 9 byte ASCII text string |
| LOGID | char(10) | 10 byte ASCII text string |

Trunk Group Exceptions database item table (Continued)

| Database item | Column type | Length |
|---------------|-------------|----------------------|
| ROW_DATE | date | 4 byte Informix date |
| ROW_TIME | smallint | 2 bytes |
| SEQNO | integer | 4 bytes |
| THRESHOLD | smallint | 2 bytes |
| TIME | smallint | 2 bytes |
| TKGRP | smallint | 2 bytes |

VDN Exceptions database items

The VDN Exceptions database items apply to the VDN Exceptions (**vdnex**) table. VDN exceptions are only available with the Vectoring feature.

VDN Exceptions database item table

| Database item | Column type | Length |
|----------------|-------------|--------------------------|
| ACD (index) | smallint | 2 bytes |
| EXTYPE | smallint | 2 bytes |
| ROW_DATE | date | 4 byte Informix date |
| ROW_TIME | smallint | 2 bytes |
| SEQNO | integer | 4 bytes |
| THRESHOLD | smallint | 2 bytes |
| TIME | smallint | 2 bytes |
| VDN | char(6) | 6 byte ASCII text string |
| VECTOR | smallint | 2 bytes |

Vector Exceptions database items

The Vector Exceptions database items apply to the Vector Exceptions (**vecex**) table. Vector exceptions are only available with the Vectoring feature.

Vector Exceptions database item table

| Database item | Column type | Length |
|----------------|-------------|----------------------------|
| ACD (index) | smallint | 2 bytes |
| EXTYPE | smallint | 2 bytes |
| ROW_DATE | date | 4 byte Informix date |
| ROW_TIME | smallint | 2 bytes |
| SEQNO | integer | 4 bytes |
| THRESHOLD | smallint | 2 bytes |
| TIME | smallint | 2 bytes |
| VECTOR | smallint | 2 bytes |

Malicious Call Trace Exceptions database items

The Malicious Call Trace Exceptions database items apply to the Malicious Call Trace Exceptions (**mctex**) table.

Malicious Call Trace Exceptions database item table

| Database item | Column type | Length |
|----------------|-------------|--------------------------------|
| ACD (index) | smallint | 2 bytes |
| ANI_SID | char(8) | 8 byte ASCII text string |
| EQLOC | char(9) | 9 byte ASCII text string |
| II_DIGITS | smallint | 2 bytes |

Malicious Call Trace Exceptions database item table (Continued)

| Database item | Column type | Length |
|---------------|-------------|---------------------------------|
| LOGID | char(10) | 10 byte ASCII text string |
| ROW_DATE | date | 4 byte Informix date |
| ROW_TIME | smallint | 2 bytes |
| SEQNO | integer | 4 bytes |
| SPLIT | smallint | 2 bytes |
| TKGRP | smallint | 2 bytes |
| VDN | char(6) | 6 byte ASCII text string |

Data Collection Exceptions database items

The Data Collection Exceptions database items apply to the Data Collection Exceptions (**linkex**) table.

Data Collection Exceptions database item table

| Database item | Column type | Length |
|----------------|-------------|----------------------------|
| ACD (index) | smallint | 2 bytes |
| DURATION | integer | 4 bytes |
| REASON | smallint | 2 bytes |
| ROW_DATE | date | 4 byte Informix date |
| ROW_TIME | smallint | 2 bytes |
| SEQNO | integer | 4 bytes |
| THRESHOLD | smallint | 2 bytes |

Disk Full Exceptions database items

The Disk Full Exceptions database items apply to the Disk Full Exceptions (**fullex**) table.

Disk Full Exceptions database item table

| Database item | Description | Column type | Length |
|---------------|--|-------------|---------------------------|
| PROC_NAME | The name of the process that failed because the disk was full. | char(30) | 30 byte ASCII text string |
| ROW_DATE | The date at which the disk was full. | date | 4 byte Informix date |
| ROW_TIME | The time at which the disk was full. | smallint | 2 bytes |
| SEQNO | The sequence number of this record. | smallint | 2 bytes |
| TASK_GRP | The activity that failed because the disk was full. | char(2) | 2 byte ASCII text string |

Split/Skill database items

The Split/Skill database item descriptions apply to historical items. Historical split/skill database items apply to the following tables:

- Intrahour Split/Skill (**hsplit**)
- Daily Split/Skill (**dsplit**)
- Weekly Split/Skill (**wsplit**)
- Monthly Split/Skill (**msplit**)

Database tables

Unless indicated otherwise, all of the database items listed in the [Split/Skill database item table](#) on page 104 are included in all four tables.

Split/Skill database item table

| Database item | Data type | Column type | Length |
|----------------|-----------|--------------------------|-------------------------|
| ABNCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| ABNCALLS1-10 | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| ABNRINGCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| ABNTIME | C | integer | 4 bytes |
| ACCEPTABLE | C | integer | 4 bytes |
| ACD (index) | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| ACDAUXOUTCALLS | A | smallint | 2 bytes |
| ACDCALLS | C | integer | 4 bytes |
| | | smallint in hsplit table | 2 bytes in hsplit table |
| ACDCALLS1-10 | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| ACDCALLS_R1 | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| ACDCALLS_R2 | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |

Split/Skill database item table (Continued)

| Database item | Data type | Column type | Length |
|--------------------|-----------|-------------------|---------|
| ACDTIME | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| ACWINCALLS | C | integer | 4 bytes |
| ACWINTIME | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| ACWOUTADJCALLS | C | integer | 4 bytes |
| ACWOUTCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| ACWOUTOFFCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| ACWOUTOFFTIME | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| ACWOUTTIME | C | integer | 4 bytes |
| ACWTIME | C | integer | 4 bytes |
| ANSTIME | C | integer | 4 bytes |
| ASSISTS ASSISTS | C C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| AUXINCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| AUXINTIME | C | integer | 4 bytes |

Split/Skill database item table (Continued)

| Database item | Data type | Column type | Length |
|----------------|-----------|-------------------|---------|
| AUXOUTADJCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| AUXOUTCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| AUXOUTOFFCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| AUXOUTOFFTIME | C | integer | 4 bytes |
| AUXOUTTIME | C | integer | 4 bytes |
| BACKUPCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| BUSYCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| BUSYTIME | C | integer | 4 bytes |
| CALLSOFFERED | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| CONFERENCE | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| DA_ACWINCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| DA_ACWINTIME | C | integer | 4 bytes |

Split/Skill database item table (Continued)

| Database item | Data type | Column type | Length |
|------------------|-----------|-------------------|---------|
| DA_ACWOCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| DA_ACWOTIME | C | integer | 4 bytes |
| DEQUECALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| DEQUETIME | C | integer | 4 bytes |
| DISCCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| DISCTIME | C | integer | 4 bytes |
| EVENT1-9 | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| HIGHCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| HOLDABNCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| HOLDCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| HOLDTIME | C | integer | 4 bytes |
| I_ACDAUXINTIME | C | integer | 4 bytes |
| I_ACDAUX_OUTTIME | C | integer | 4 bytes |
| I_ACDOOTHERTIME | C | integer | 4 bytes |
| I_ACDTIME | C | integer | 4 bytes |

Split/Skill database item table (Continued)

| Database item | Data type | Column type | Length |
|----------------|-----------|-------------|---------|
| I_ACDDTIME_R1 | C | integer | 4 bytes |
| I_ACDDTIME_R2 | C | integer | 4 bytes |
| I_ACWINTIME | C | integer | 4 bytes |
| I_ACWOUTTIME | C | integer | 4 bytes |
| I_ACWTIME | C | integer | 4 bytes |
| I_ACWTIME_R1 | C | integer | 4 bytes |
| I_ACWTIME_R2 | C | integer | 4 bytes |
| I_ARRIVED | C | integer | 4 bytes |
| I_AUXINTIME | C | integer | 4 bytes |
| I_AUXOUTTIME | C | integer | 4 bytes |
| I_AUXTIME | C | integer | 4 bytes |
| I_AUXTIME0 | C | integer | 4 bytes |
| I_AUXTIME1-9 | C | integer | 4 bytes |
| I_AVAILTIME | C | integer | 4 bytes |
| I_DA_ACDDTIME | C | integer | 4 bytes |
| I_DA_ACWTIME | C | integer | 4 bytes |
| I_NORMTIME | C | integer | 4 bytes |
| I_OL1TIME | C | integer | 4 bytes |
| I_OL2TIME | C | integer | 4 bytes |
| I_OTHERTIME | C | integer | 4 bytes |
| I_OTHERTIME_R1 | C | integer | 4 bytes |
| I_OTHERTIME_R2 | C | integer | 4 bytes |
| I_RINGTIME | C | integer | 4 bytes |
| I_RINGTIME_R1 | C | integer | 4 bytes |
| I_RINGTIME_R2 | C | integer | 4 bytes |
| I_STAFFTIME | C | integer | 4 bytes |

Split/Skill database item table (Continued)

| Database item | Data type | Column type | Length |
|----------------|-----------|---------------------------|---------|
| I_TAUXTIME | C | integer | 4 bytes |
| I_TAVAILTIME | C | integer | 4 bytes |
| INCOMPLETE | C | smallint | 2 bytes |
| INFLOWCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| INTERFLOWCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| INTRVL | A | smallint (only in hsplit) | 2 bytes |
| LOWCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| MAXINQUEUE | M | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| MAXOCWTIME | M | integer | 4 bytes |
| MAXSTAFFED | M | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| MAXTOP | M | integer | 4 bytes |
| MEDCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| NOANSREDIR | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |

Split/Skill database item table (Continued)

| Database item | Data type | Column type | Length |
|---------------|-----------|-------------------|---------|
| O_ABNCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| O_ACDCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| O_ACDTIME | C | integer | 4 bytes |
| O_ACWTIME | C | integer | 4 bytes |
| O_OTHERCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| OTHERCALLS | C | integer | 4 bytes |
| OTHERTIME | C | integer | 4 bytes |
| OUTFLOWCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| OUTFLOWTIME | C | integer | 4 bytes |
| PERIOD1-9 | A | smallint | 2 bytes |
| PERIODCHG | A | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| PHANTOMABNS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| RINGCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| RINGTIME | C | integer | 4 bytes |

Split/Skill database item table (Continued)

| Database item | Data type | Column type | Length |
|---------------------|-----------|------------------------------------|-----------------------------|
| ROW_DATE (index) | I | date | 4 bytes Informix date |
| RSV_LEVEL | | smallint | 2 bytes |
| SERVICELEVEL | A | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| SLVLABNS | C | integer | 4 bytes |
| SLVLOUTFLOWS | C | integer | 4 bytes |
| SPLIT (index) | I | smallint | 2 bytes |
| STARTTIME | I | smallint (only in hsplit table) | 2 bytes |
| SVCLEVELCHG | A | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| TOPCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| TRANSFERRED | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |

Trunk Group database items

The Trunk Group database item descriptions apply to historical items. Historical trunk group database items apply to the Intrahour Trunk Group (**htkgrp**), Daily Trunk Group (**dtkgrp**), Weekly Trunk Group (**wtkgrp**), and Monthly Trunk Group (**mtkgrp**) tables.

Database tables

Unless indicated otherwise, items listed in the [Trunk Group database item table](#) on page 112 are included in all four tables.

Trunk Group database item table

| Database item | Data type | Column type | Length |
|---------------|-----------|-------------------|---------|
| ABNCALLS | C | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| ABNQUECALLS | C | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| ABNRINGCALLS | C | integer | 4 bytes |
| ABNVECCALLS | C | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| ACD (index) | I | smallint | 2 bytes |
| ACDCALLS | C | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| ACDCALLS_R1 | C | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| ACDCALLS_R2 | C | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| ALLINUSETIME | C | integer | 4 bytes |
| AUDIO | C | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| BACKUPCALLS | C | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |

Trunk Group database item table (Continued)

| Database item | Data type | Column type | Length |
|-----------------|-----------|--------------------------------|---------|
| BH_ABNCALLS | B | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| BH_ACDCALLS | B | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| BH_ALLINUSETIME | B | integer | 4 bytes |
| BH_BUSYCALLS | B | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| BH_DISCCALLS | B | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| BH_INCALLS | B | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| BH_INTERVAL | B | integer (only in dtkgrp table) | 4 bytes |
| BH_INTIME | B | integer | 4 bytes |
| BH_OABNCALLS | B | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| BH_OACDCALLS | B | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| BH_OOTHERCALLS | B | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |

Trunk Group database item table (Continued)

| Database item | Data type | Column type | Length |
|---------------|-----------|-------------------|---------|
| BH_OTHERCALLS | B | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| BH_OUTCALLS | B | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| BH_OUTTIME | B | integer | 4 bytes |
| BH_STARTTIME | B | integer | 4 bytes |
| BLOCKAGE | C | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| BUSYCALLS | C | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| COMPLETED | C | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| CONNECTCALLS | C | integer | 4 bytes |
| DISCCALLS | C | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| FAILURES | C | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| I_INOCC | C | integer | 4 bytes |
| I_OUTOCC | C | integer | 4 bytes |
| INCALLS | C | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |

Trunk Group database item table (Continued)

| Database item | Data type | Column type | Length |
|---------------------|-----------|------------------------------------|----------------------------|
| INCOMPLETE | C | smallint | 2 bytes |
| INTIME | C | integer | 4 bytes |
| INTRVL | A | smallint (only in htkgrp table) | 2 bytes |
| MBUSYTIME | C | integer | 4 bytes |
| O_ABNCALLS | C | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| O_ACDCALLS | C | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| O_OTHERCALLS | C | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| OTHERCALLS | C | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| OUTCALLS | C | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| OUTTIME | C | integer | 4 bytes |
| ROW_DATE (index) | I | date | 4 byte Informix date |
| SETUPTIME | C | integer | 4 bytes |
| SHORTCALLS | C | integer | 4 bytes |
| SPLIT | A | smallint | 2 bytes |
| TKGRP (index) | I | smallint | 2 bytes |

Trunk Group database item table (Continued)

| Database item | Data type | Column type | Length |
|---------------|-----------|-------------------|--------------------------|
| TRANSFERRED | C | integer | 4 bytes |
| | | smallint (htkgrp) | 2 bytes |
| TRUNKS | A | smallint | 2 bytes |
| VDN | A | char(6) | 6 byte ASCII text string |
| VECTOR | A | smallint | 2 bytes |

Trunk database items

The Trunk database item descriptions apply to historical items. Historical trunk database items apply to the Intrahour Trunk (**htrunk**), Daily Trunk (**dtrunk**), Weekly Trunk Group (**wtrunk**), and Monthly Trunk (**mtrunk**) tables. Unless indicated otherwise, all items listed in the [Trunk database item table](#) on page 116 are included in all four tables.

Trunk database item table

| Database item | Data type | Column type | Length |
|---------------|-----------|-------------------|---------|
| ABNCALLS | C | integer | 4 bytes |
| | | smallint (htrunk) | 2 bytes |
| ACD (index) | I | smallint | 2 bytes |
| ACDCALLS | C | integer | 4 bytes |
| | | smallint (htrunk) | 2 bytes |
| ACDCALLS_R1 | C | integer | 4 bytes |
| | | smallint (htrunk) | 2 bytes |

Trunk database item table (Continued)

| Database item | Data type | Column type | Length |
|---------------|-----------|---------------------------------|--------------------------|
| ACDCALLS_R2 | C | integer | 4 bytes |
| | | smallint (htrunk) | 2 bytes |
| AUDIO | C | integer | 4 bytes |
| | | smallint (htrunk) | 2 bytes |
| EQLOC (index) | A | char(8) | 8 byte ASCII text string |
| FAILURES | C | integer | 4 bytes |
| | | smallint (htrunk) | 2 bytes |
| I_INOCC | C | integer | 4 bytes |
| | | smallint (htrunk) | 2 bytes |
| I_OUTOCC | C | integer | 4 bytes |
| | | smallint (htrunk) | 2 bytes |
| INCALLS | C | integer | 4 bytes |
| | | smallint (htrunk) | 2 bytes |
| INCOMPLETE | C | smallint | 2 bytes |
| INTIME | C | integer | 4 bytes |
| | | smallint (htrunk) | 2 bytes |
| INTRVL | A | smallint (only in htrunk table) | 2 bytes |
| LOC_ID | C | integer | 4 bytes |

Trunk database item table (Continued)

| Database item | Data type | Column type | Length |
|---------------------|-----------|-------------------|----------------------|
| MBUSYTIME | C | integer | 4 bytes |
| | | smallint (htrunk) | 2 bytes |
| O_ABNCALLS | C | integer | 4 bytes |
| | | smallint (htrunk) | 2 bytes |
| O_ACDCALLS | C | integer | 4 bytes |
| | | smallint (htrunk) | 2 bytes |
| O_OTHERCALLS | C | integer | 4 bytes |
| | | smallint (htrunk) | 2 bytes |
| OUTCALLS | C | integer | 4 bytes |
| | | smallint (htrunk) | 2 bytes |
| OTHERCALLS | C | integer | 4 bytes |
| | | smallint (htrunk) | 2 bytes |
| OUTTIME | C | integer | 4 bytes |
| | | smallint (htrunk) | 2 bytes |
| ROW_DATE (index) | I | date | 4 byte Informix date |
| SHORTCALLS | C | integer | 4 bytes |
| | | smallint (htrunk) | 2 bytes |
| TKGRP (index) | A | smallint | 2 bytes |

Vector database items

The Vector database item descriptions apply to historical items. Vector database items are only available if you purchased the optional Vectoring feature.

Historical vector database items apply to the Intrahour Vector (**hvector**), Daily Vector (**dvector**), Weekly Vector (**wvector**), and Monthly Vector (**mvector**) tables. Unless indicated otherwise, all items listed in the [Vector database item table](#) on page 119 are included in all four tables.

Vector database item table

| Database item | Data type | Column type | Length |
|---------------|-----------|--------------------|---------|
| ABNCALLS | C | integer | 4 bytes |
| | | smallint (hvector) | 2 bytes |
| ABNQUECALLS | C | integer | 4 bytes |
| | | smallint (hvector) | 2 bytes |
| ABNRINGCALLS | C | integer | 4 bytes |
| | | smallint (hvector) | 2 bytes |
| ABNTIME | C | integer | 4 bytes |
| ACD (index) | I | smallint | 2 bytes |
| ACDCALLS | C | integer | 4 bytes |
| | | smallint (hvector) | 2 bytes |
| ACDCALLS_R1 | C | integer | 4 bytes |
| | | smallint (hvector) | 2 bytes |
| ACDCALLS_R2 | C | integer | 4 bytes |
| | | smallint (hvector) | 2 bytes |

Vector database item table (Continued)

| Database item | Data type | Column type | Length |
|---------------|-----------|--------------------|---------|
| ADJATTEMPTS | C | integer | 4 bytes |
| | | smallint (hvector) | 2 bytes |
| ADJROUTED | C | integer | 4 bytes |
| | | smallint (hvector) | 2 bytes |
| ANSTIME | C | integer | 4 bytes |
| BACKUPCALLS | C | integer | 4 bytes |
| | | smallint (hvector) | 2 bytes |
| BUSYCALLS | C | integer | 4 bytes |
| | | smallint (hvector) | 2 bytes |
| BUSYTIME | C | integer | 4 bytes |
| DEFLECTCALLS | C | integer | 4 bytes |
| | | smallint (hvector) | 2 bytes |
| DISCCALLS | C | integer | 4 bytes |
| | | smallint (hvector) | 2 bytes |
| DISCTIME | C | integer | 4 bytes |
| GOTOCALLS | C | integer | 4 bytes |
| | | smallint (hvector) | 2 bytes |
| GOTOTIME | C | integer | 4 bytes |
| INCALLS | C | integer | 4 bytes |
| | | smallint (hvector) | 2 bytes |
| INCOMPLETE | C | smallint | 2 bytes |

Vector database item table (Continued)

| Database item | Data type | Column type | Length |
|----------------|-----------|-------------------------------|---------|
| INFLOWCALLS | C | integer | 4 bytes |
| | | smallint (hvector) | 2 bytes |
| INTERFLOWCALLS | C | integer | 4 bytes |
| | | smallint (hvector) | 2 bytes |
| INTIME | C | integer | 4 bytes |
| INTRVL | A | smallint (only in hvdn table) | 2 bytes |
| LOOKATTEMPTS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| LOOKFLOWCALLS | C | integer | 4 bytes |
| | | smallint (hvector) | 2 bytes |
| NETDISCCALLS | C | integer | 4 bytes |
| | | smallint (hvector) | 2 bytes |
| NETPOLLS | C | integer | 4 bytes |
| | | smallint (hvector) | 2 bytes |
| OTHERCALLS | C | integer | 4 bytes |
| | | smallint (hvector) | 2 bytes |
| OTHERTIME | C | integer | 4 bytes |
| OUTFLOWCALLS | C | integer | 4 bytes |
| | | smallint (hvector) | 2 bytes |
| OUTFLOWTIME | C | integer | 4 bytes |

Vector database item table (Continued)

| Database item | Data type | Column type | Length |
|---------------------|-----------|-----------------------|----------------------------|
| PHANTOMABNS | C | integer | 4 bytes |
| RINGCALLS | C | integer | 4 bytes |
| | | smallint (hvector) | 2 bytes |
| RINGTIME | C | integer | 4 bytes |
| ROW_DATE (index) | I | date | 4 byte Informix date |
| VDISCCALLS | C | integer | 4 bytes |
| | | smallint (hvector) | 2 bytes |
| VECTOR (index) | I | smallint | 2 bytes |

VDN database items

The VDN Database item descriptions apply to historical items. VDN database items are only available if you purchased the optional Vectoring feature.

Historical VDN database items apply to the Intrahour VDN (**hvdn**), Daily VDN (**dvdn**), Weekly VDN (**wvdn**), and Monthly VDN (**mvdn**) tables. Unless indicated otherwise, all items listed in the [VDN database item table](#) on page 122 are included in all four tables.

VDN database item table

| Database item | Data type | Column type | Length |
|---------------|-----------|--------------------|---------|
| ABNCALLS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| ABNCALLS1-10 | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |

VDN database item table (Continued)

| Database item | Data type | Column type | Length |
|---------------|-----------|-----------------|---------|
| ABNQUECALLS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| ABNRINGCALLS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| ABNTIME | C | integer | 4 bytes |
| ACCEPTABLE | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| ACD (index) | I | smallint | 2 bytes |
| ACDCALLS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| ACDCALLS _R1 | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| ACDCALLS _R2 | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| ACDTIME | C | integer | 4 bytes |
| ACWTIME | C | integer | 4 bytes |
| ADJATTEMPTS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| ADJROUTED | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |

VDN database item table (Continued)

| Database item | Data type | Column type | Length |
|-------------------|-----------|------------------------------|---------|
| ANSCONNCALLS 1-10 | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| ANSTIME | C | integer | 4 bytes |
| BACKUPCALLS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| BH_ABNCALLS | B | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| BH_ACDCALLS | B | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| BH_ACDDTIME | B | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| BH_BUSYCALLS | B | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| BH_DISCCALLS | B | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| BH_INTERVAL | B | integer (only in dvdn table) | 4 bytes |
| BH_OTHERCALLS | B | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| BH_STARTTIME | B | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |

VDN database item table (Continued)

| Database item | Data type | Column type | Length |
|---------------|-----------|-----------------|---------|
| BH_VDNCALLS | B | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| BSRPLAN | A | smallint | 2 bytes |
| BUSYCALLS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| BUSYTIME | C | integer | 4 bytes |
| CONNECTCALLS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| CONNECTTIME | C | integer | 4 bytes |
| CONNTALKTIME | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| DEFLECTCALLS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| DISCCALLS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| DISCTIME | C | integer | 4 bytes |
| HOLDABNCALLS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| HOLDACDCALLS | C | integer | 4 bytes |
| HOLDACDTIME | C | integer | 4 bytes |

VDN database item table (Continued)

| Database item | Data type | Column type | Length |
|----------------|-----------|-------------------------------|---------|
| HOLDCALLS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| HOLDTIME | C | integer | 4 bytes |
| I_ARRIVED | C | integer | 4 bytes |
| INCALLS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| INCOMPLETE | C | smallint | 2 bytes |
| INFLOWCALLS | C | integer | 4 bytes |
| | | smallint (hsplit) | 2 bytes |
| INTERFLOWCALLS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| INTIME | C | integer | 4 bytes |
| INTRVL | A | smallint (only in hvdn table) | 2 bytes |
| LOOKATTEMPTS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| LOOKFLOWCALLS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| MAXOCWTIME | M | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |

VDN database item table (Continued)

| Database item | Data type | Column type | Length |
|---------------|-----------|-----------------|---------|
| MAXWAITING | M | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| NETDISCCALLS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| NETINCALLS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| NETINTIME | C | integer | 4 bytes |
| NETPOLLS | C | integer | 4 bytes |
| NOANSREDIR | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| NUMTGS | A | integer | 4 bytes |
| OTHERCALLS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| OTHERTIME | C | integer | 4 bytes |
| OUTFLOWCALLS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| OUTFLOWTIME | C | integer | 4 bytes |
| PERIOD1-9 | A | smallint | 2 bytes |
| PERIODCHG | A | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |

VDN database item table (Continued)

| Database item | Data type | Column type | Length |
|------------------|-----------|-----------------|----------------------|
| PHANTOMABNS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| RETURNCALLS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| RINGCALLS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| RINGTIME | C | integer | 4 bytes |
| ROW_DATE (index) | I | date | 4 byte Informix date |
| SERVICELEVEL | A | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| SKILLACWTIME1-3 | C | integer | 4 bytes |
| SKILLCALLS1-3 | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| SKILLTIME1-3 | C | integer | 4 bytes |
| SKILL1-3 | A | smallint | 2 bytes |
| SLVLABNS | C | integer | 4 bytes |
| SLVLOUTFLOWS | C | integer | 4 bytes |
| SVCLEVELCHG | A | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| TRANSFERRED | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |

VDN database item table (Continued)

| Database item | Data type | Column type | Length |
|----------------|-----------|-----------------|--------------------------|
| VDISCCALLS | C | integer | 4 bytes |
| | | smallint (hvdn) | 2 bytes |
| VDN (index) | I | char(6) | 6 byte ASCII text string |
| VECTOR (index) | A | smallint | 2 bytes |

Forecasting database tables

The Forecasting database tables are only available if you purchased the optional Avaya CMS Forecast package.

This section contains the following topics:

- [Current Day Configuration database items](#) on page 129
- [Current Day Report database items](#) on page 130

Current Day Configuration database items

The Current Day Configuration database items apply to the Current Day (**f_cday**) table.

Current Day Configuration database item table

| Database item | Column type | Length |
|---------------|-------------|-------------------------------------|
| ACD (index) | smallint | 2 bytes |
| CHANGE | smallfloat | 4 byte Informix floating point type |
| CHPROF | smallint | 2 bytes |
| FMETHOD | smallint | 2 bytes |

Current Day Configuration database item table (Continued)

| Database item | Column type | Length |
|---------------------|-------------|----------------------|
| HDATE1-4 | date | 4 byte Informix date |
| ROW_DATE (index) | date | 4 byte Informix date |
| SPLIT (index) | smallint | 2 bytes |
| TRENDBASE | date | 4 byte Informix date |
| WT1-4 | smallint | 2 bytes |

Current Day Report database items

The Current Day Report database items apply to the Current Day Report (**f_cdayrep**) table.

Current Day Forecast Report database item table

| Database item | Column type | Length |
|----------------|-------------|-------------------------------------|
| ACD (index) | smallint | 2 bytes |
| AGOCC | smallfloat | 4 byte Informix floating point type |
| AVGAGSERV | smallint | 2 bytes |
| AVGSPEEDANS | smallint | 2 bytes |
| FCALLS | integer | 4 bytes |
| INTRVL | smallint | 2 bytes |
| NUMAGREQ | smallint | 2 bytes |
| RAGOCC | smallfloat | 4 byte Informix floating point type |

Current Day Forecast Report database item table (Continued)

| Database item | Column type | Length |
|---------------------|-------------|--|
| RAVGSPEEDANS | smallint | 2 bytes |
| ROW_DATE (index) | date | 4 byte Informix date |
| RSERVLEVELP | smallfloat | 4 byte Informix floating point type |
| SERVLEVELP | smallfloat | 4 byte Informix floating point type |
| SERVLEVELT | smallint | 2 bytes |
| SPLIT (index) | smallint | 2 bytes |
| STARTTIME | smallint | 2 bytes |

Administrative database tables

Administrative database tables require read permission from the Maintenance sub-menu. Most of these database items require you to enter additional information in order to become functional. Administrative database tables are available with any CMS or switch release.

This section contains the following topics:

- [Data Collection Period database items](#) on page 132
- [Archiver Execution Status database items](#) on page 133
- [Customer Log database items](#) on page 133
- [Agent Group database items](#) on page 134
- [Synonyms database items](#) on page 135
- [ACD Shifts database items](#) on page 136
- [Database Items](#) on page 136

Data Collection Period database items

The Administrative data collection period database items apply to the Daily Data Collection Period (**d_secs**), Weekly Data Collection Period (**w_secs**), and Monthly Data Collection Period (**m_secs**) tables. The tables indicate the number of seconds in the data collection period (daily, weekly, monthly).

Unless indicated otherwise, all items listed in the [Data Collection Period database item table](#) on page 132 are included in all three tables.

Data Collection Period database item table

| Database item | Description | Data type | Column type | Length |
|----------------|---|-----------|-----------------------------------|----------------------|
| ACD (index) | The ACD number for which data was collected. | A | smallint | 2 bytes |
| ROW_DATE | The day for which data was collected or the exception occurred. | A | date | 4 byte Informix date |
| SECSPERDAY | The number of seconds in the daily data collection period | A | integer (only in d_secs table) | 4 bytes |
| SECSPERMN | The number of seconds in the monthly data collection period. | A | integer (only in m_secs table) | 4 bytes |
| SECSPERWK | The number of seconds in the weekly data collection period. | A | integer (only in w_secs table) | 4 bytes |

Archiver Execution Status database items

The Archiver Execution Status database item descriptions apply specifically to items in the Archiver Execution Status (**arch_stat**) table. The table contains status information on recent archiver executions, and displays status and the next run scheduled.

Archiver Execution Status database item table

| Database item | Description | Data type | Column type | Length |
|----------------------|---|-----------|-------------|---------------------------|
| ACD (index) | The ACD number for which data was collected. | A | smallint | 2 bytes |
| ARCH_TYPE (index) | The type of archiver executions being run. Values are: 1 = interval, 2 = daily, 3 = weekly, 4 = monthly. | A | char(20) | 20 byte ASCII text string |
| LAST_TIME | The last time the archiver execution was run. | A | char(20) | 20 byte ASCII text string |
| STATUS | The status of the archiver execution. This field indicates if the execution was not run, is currently running, or has finished. Values are: 1 = not run 2 = finished, the archive was successful 3 = finished, the archive had a failure 4 = running If the status field displays 3, for finished, but had a failure, you should consult the error log (customer_log table) and the archive log for the reason prior to troubleshooting. | A | char(9) | 9 byte ASCII text string |

Customer Log database items

The Customer Log database items apply to the Customer Log (**customer_log**) table. The table contains customer error log information on recent archiver executions. The information includes the error code, the date the error occurred, the severity, the

Database tables

associated event, and a description of the error. The Customer Log table is not backed up by the CMS Maintenance backup.

Customer Log database item table

| Database item | Description | Data type | Column type | Length |
|---------------|--|-----------|-------------|----------------------------|
| ACD_ID | The ACD number for which data was collected. | A | integer | 4 bytes |
| COUNTS | The number of occurrences of the error. | A | integer | 4 bytes |
| DATE_OCCURRED | The date that the error occurred. | A | date | 4 byte Informix date |
| DESCRIPTION | A text description of the error. | A | char(256) | 256 byte ASCII text string |
| ERROR_CODE | The error code number. | A | integer | 4 bytes |
| LAST_TIME | The last time the error occurred. | A | integer | 4 bytes |
| SEVERITY | The level of severity of the error. | A | char(10) | 10 byte ASCII text string |

Agent Group database items

The Agent Group database items apply to the Agent Group (**agroups**) table. The table contains dictionary information on agent groups.

Agent Group database item table

| Database item | Description | Data type | Column type | Length |
|----------------------|--|-----------|-------------|---------------------------|
| ACD_NO (index) | The ACD number for which data was collected. | A | smallint | 2 bytes |
| ITEM_TYPE (index) | The type "agent group." | A | char(20) | 20 byte ASCII text string |

Agent Group database item table (Continued)

| Database item | Description | Data type | Column type | Length |
|----------------------|---|-----------|-------------|---------------------------------|
| ITEM_NAME (index) | The name of the agent group. | A | char(20) | 20 byte ASCII text string |
| VALUE (index) | An agent login ID belonging to the agent group. | A | char(9) | 9 byte ASCII text string |

Synonyms database items

The Synonyms database items apply to items in the Synonyms (**synonyms**) table. The table contains dictionary synonyms.

Synonyms database item table

| Database item | Description | Data type | Column type | Length |
|----------------------|---|-----------|--|---------------------------------|
| ACD_NO (index) | The ACD number for which data was collected. | A | smallint | 2 bytes |
| DESCR | The description, or definition, of the dictionary synonym. | A | char(150) | 5 byte ASCII text string |
| ITEM_TYPE (index) | The type of synonym. | A | char(20) | 20 byte ASCII text string |
| ITEM_NAME (index) | The name of the synonym. There can be many ITEM_NAMEs for a specific ITEM_TYPE. | A | char(60) (Only first 20 are significant) | 60 byte ASCII text string |
| STANDARD | This item indicates if the item is a standard or custom synonym. Values are: 1 = standard, not 1 = custom. | A | smallint | 2 bytes |
| VALUE (index) | The item name's corresponding value. Because each ITEM_TYPE can have many different ITEM_NAMEs, a discrete value is assigned to each synonym ITEM_NAME. | A | char(40) (Only first 9 are significant) | 40 byte ASCII text string |

Database tables

ACD Shifts database items

The ACD Shifts database items apply to the ACD Shifts (**acd_shifts**) table. The table contains information on ACD shift times and the maximum number of agents logged in for each shift.

ACD Shifts database item table

| Database item | Description | Data type | Column type | Length |
|----------------|---|-----------|-------------|---------|
| ACD (index) | The ACD number for which data was collected. | A | smallint | 2 bytes |
| SHIFT_ID | The identification number of the ACD shift. Values are 1 - 4. | A | smallint | 2 bytes |
| START_TIME | The ACD shift start time. | A | smallint | 2 bytes |
| STOP_TIME | The ACD shift stop time. | A | smallint | 2 bytes |
| MAX_AGENTS | The maximum number of agents logged in per shift. | A | smallint | 2 bytes |

Database Items

Database Items applies to items in the Database Items (**dbitems**) table. The table contains definitions for:

- Dictionary standard and custom database items
- Constants
- Calculations

Database Items table

| Database item | Description | Data type | Column type | Length |
|----------------------|--|-----------|-------------|---------------------------------|
| ITEM_TYPE (index) | The type of data for the row. Valid values are: dbase = database item calc = calculation constant = constant cust_def = customer-defined database item | A | char(8) | 8 byte ASCII text string |
| ITEM_NAME (index) | The name of the data item. There can be many ITEM_NAMES for a specific ITEM_TYPE. | A | char(20) | 20 byte ASCII text string |

Database Items table (Continued)

| Database item | Description | Data type | Column type | Length |
|---------------|--|-----------|-------------|---------------------------|
| FORMULA | The formula for the database constant or calculation. | A | char(70) | 70 byte ASCII text string |
| STANDARD | This item indicates if the item is a standard or custom database item. Values are: 1 = standard, not 1 (null) = custom. | A | smallint | 2 bytes |
| DESCR | The description of the database calculation, constant, or standard/custom database item. | A | char(50) | 50 byte ASCII text string |

Generating a CMS database schema

This section explains how to generate the schema definition information of the CMS database.

This section contains the following topics:

- [Generating the schema for the entire CMS database](#) on page 138
- [About the dbschema command](#) on page 139

Generating the schema for the entire CMS database

To generate the CMS database schema:

1. Log into the system as **root**.
2. Choose one of the following options to set the Informix environment:
 - If your system is running CMS R3V9 or later, enter the following command:

```
. /opt/informix/bin/setenv
```

- If your system is running CMS R3V8 or earlier, enter the following commands:

```
INFORMIXDIR=/opt/informix
```

```
export INFORMIXDIR
```

```
PATH=$PATH:$INFORMIXDIR/bin
```

```
export PATH
```

```
INFORMIXSERVER=cms_se;export INFORMIXSERVER
```

```
DB_LOCALE=en_us.utf8; export DB_LOCALE
```

3. Enter:

```
cd /tmp
```

Note:

You can use a different directory to contain your database schema with one exception. Never use the **root (/)** directory to store a database schema. A database schema can be very large and will use up all of the disk space allocated to the **root** directory. If the **root** directory does not have enough disk space, the CMS system will not function correctly.

4. Enter:

```
dbschema -d cms cms.sql
```

The system saves the CMS database schema in the **/tmp** directory as a file named **cms.sql**.

Note:

You can use different options to modify the `dbschema` command used in Step 4. For more information, see [About the dbschema command](#) on page 139.

About the dbschema command

You can modify the `dbschema` command using additional command options.

For more information about the `dbschema` command options:

1. Log into the system as **root**.
2. Choose one of the following options to set the Informix environment:
 - If your system is running CMS R3V9 or later, enter the following command:


```
. /opt/informix/bin/setenv
```
 - If your system is running CMS R3V8 or earlier, enter the following commands:


```
INFORMIXDIR=/opt/informix
export INFORMIXDIR
PATH=$PATH:$INFORMIXDIR/bin
export PATH
INFORMIXSERVER=cms_se;export INFORMIXSERVER
DB_LOCALE=en_us.utf8; export DB_LOCALE
```

3. Enter:

```
dbschema
```

The system displays all of the options that you can use to modify the `dbschema` command.

Database tables

Glossary

| | |
|---|--|
| Abandoned call | A call in which a caller hangs up before receiving an answer from an agent. The call could be queued to a split/skill or in a vector/vector directory number (VDN) or ringing at an agent before it is abandoned. |
| Access permissions | Permissions assigned to a Call Management System (CMS) user so that the user can access different subsystems in CMS or administer specific elements (splits/skills, trunks, vectors, and so on) of the ACD. Access permissions are specified as read or write permission. Read permission means the CMS user can access and view data (for example, run reports or view the Dictionary subsystem). Write permission means the CMS user can add, modify, or delete data and execute processes. |
| ACD | See Automatic Call Distribution. |
| ACD call | A call that queued to a split/skill and was answered by an agent in that split/skill, or a call that queued as a direct agent call and was answered by the agent for whom it was queued. |
| ACW | See After Call Work. |
| Adjunct/Switch Applications Interface (ASAI) | An open application interface through which processors and switches can jointly provide services that require applications to initiate, receive, and control calls or make use of switch features. (See Open Application Interface.) |
| After Call Work (ACW) | An agent state generally representing work related to the preceding ACD call. |
| API | See Application Programming Interface. |
| Application Programming Interface (API) | A set of related functions that a computer programmer uses to obtain some kind of service from another piece of software. Programmers of Windows based applications use the Windows API to create windows, draw text on the screen, access files, and perform all other services provided by Windows. Despite the use of the word application in this term, applications might not be the only software using an API; lower-level software components such as network drivers also have APIs, but these components are not “applications” and are not used directly by applications. |
| ASAI | See Adjunct/Switch Applications Interface. |
| Automatic Call Distribution (ACD) | A switch feature using software that channels high-volume incoming and outgoing call traffic to agent groups (splits or skills). Also an agent state where the extension is engaged on an ACD call. |

Backup

| | |
|--|---|
| Backup | The process of protecting data by writing the contents of the disk to an archive (or tape) that can be removed from the computer environment and stored safely. |
| Calculation | The abbreviated name (calculation name) for the formula calculation that generates the data for a field in a report. |
| Call Management System (CMS) | A software product used by business customers that have Avaya telecommunications switches and receive a large volume of telephone calls that are processed through the Automatic Call Distribution (ACD) feature of the switch. The CMS collects call-traffic data, formats management reports, and provides an administrative interface to the ACD feature in the switch. |
| Call Management System Query Language (CMSQL) | A tool that allows direct queries of the historical database. This tool is the interactive interface typically used to view the Informix database. For CMS purposes, CMSQL is used instead of Informix SQL. |
| Call Vectoring | <p>A switch feature that provides a highly flexible method for processing ACD calls.</p> <p>A call vector is a set of instructions that controls the routing of incoming and outgoing calls based on current conditions. Examples of call vector conditions include time of day and the number of calls in queue.</p> |
| Call Work Code (CWC) | An ACD capability that allows the agent to enter a string of digits during or after the call and send them to CMS for management reporting. |
| Avaya Supervisor | The Call Management System application for the Microsoft Windows operating environment. |
| CMS | See Call Management System. |
| Current interval | Represents the current intrahour interval, which can be 15, 30, or 60 minutes. The current interval is part of the real-time database. CMS starts collecting ACD cumulative data at the beginning of the interval (on the hour, half-hour, or quarter hour) and continues collecting ACD cumulative data until the end of the interval. When the current interval changes, all cumulative data is cleared and CMS begins counting cumulative data again starting from zero. The length of the interval is set in the System Setup: Storage Intervals window and is called the <i>intrahour interval</i> . |
| CWC | See Call Work Code. |
| Daily data | Interval data that has been converted to a 1-day summary. |
| CMS database | A group of files that store ACD data according to a specific time frame: current and previous intrahour real-time data and intrahour, daily, weekly, and monthly historical data. |

| | |
|--|--|
| Database item | A name for a specific type of data stored in one of the CMS databases. A database item may store ACD identifiers (split numbers or names, login IDs, VDNs, and so on) or statistical data on ACD performance (number of ACD calls, wait time for calls in queue, current states of individual agents and so on). |
| Database Management System (DBMS) | The software that manages access to structured data. For example, the Microsoft SQL Server is a database management system. Database management system can also be used generally to include PC database products such as Microsoft Access, as well as any other software that can provide data access services. |
| CMS database tables | CMS uses these tables to collect, store, and retrieve ACD data. Standard CMS items (database items) are names of columns in the CMS database tables. |
| DBMS | See Database Management System. |
| Dictionary | A CMS subsystem that can be used to assign names to various call center elements such as login IDs, splits/skills, trunk groups, VDNs and vectors. These names are displayed on reports, making them easier to interpret. Dictionary also allows customized calculations to be created for use in reports. |
| Driver manager | A dynamic link library that loads drivers on behalf of an application. |
| Dynamic link library | A dynamic link library is another name for a driver or a driver manager. A dynamic link library is specific to the DBMS of the data being accessed. For example, an Informix specific dynamic link library will be used to access data in an Informix database, such as the CMS database. |
| Entity | A generic term that refers to one of the following: Agent, Split/Skill, Trunk, Trunk Group, VDN, or Vector. |
| Exception | A type of activity in the ACD which falls outside the limits you have defined. An exceptional condition is defined in the CMS Exceptions subsystem, and usually indicates abnormal or unacceptable performance of the ACD (by agents, splits/skills, VDNs, vectors, trunks, or trunk groups). |
| Historical database | A database that contains intrahour records for up to 62 days, daily records for up to 5 years, and weekly/monthly records for up to 10 years for each CMS table. |
| Historical reports | Reports that display past ACD data for various CMS tables. |
| Informix | A relational database management system used to organize CMS historical data. |
| Informix SQL | A query language tool that is used to extract data from an Informix database. |
| Intrahour interval | A 15-, 30-, or 60-minute segment of time starting on the hour. An intrahour interval is the basic unit of CMS report time. |

| | |
|--|---|
| LAN | |
| LAN | See <i>Local Area Network</i> . |
| Local area network (LAN) | A private interactive communication network that allows computers to communicate over short distances, usually less than one mile, at high data transfer rates from 1 Mbps to as high as 100 Mbps. |
| Monthly data | Daily data that has been converted to a monthly summary. |
| Multi-tier driver | OpenLink Multi-Tier drivers feature a Generic Driver installed on the client, a Request Broker and Database Agent installed on the server, and use OpenLink Database Independent Networking. The Multi-Tier drivers are more sophisticated than the Single-Tier drivers as they have been developed with enterprise-wide deployment in mind and feature enhancements in areas such as performance, security and configuration management. |
| ODBC | See Open Database Connectivity. |
| Open Database Connectivity (ODBC) | Open Database Connectivity is a standard application programming interface (API) for accessing data in both relational and non-relational databases. |
| Previous interval | Represents one intrahour interval and is part of the real-time database. At the end of each intrahour interval, the contents of the current intrahour interval are copied to the previous intrahour interval portion of the real-time database. |
| Read permission | The CMS user with read permission can access and view data (for example, run reports or view the Dictionary subsystem). Read permission is granted from the User Permissions subsystem. |
| Real-time database | Consists of the current and previous intrahour data on each CMS-measured agent, split/skill, trunk, trunk group, vector, and VDN. |
| Single-user mode | Only one person can log into CMS. Data continues to be collected if data collection is "on." This mode is required to change some CMS administration. |
| SQL | See Structured query language. |
| Structured query language (SQL) | A language used to interrogate and process data in a relational database (such as Informix). |
| Switch | A private switching system providing voice-only or voice and data communications services (including access to public and private networks) for a group of terminals within a customer's premises. |
| Trunk | A telephone line that carries calls between two switches, between a Central Office (CO) and a switch, or between a CO and a phone. |

| | |
|--------------------------------------|---|
| Trunk group | A group of trunks that are assigned the same dialing digits - either a phone number or a Direct Inward Dialed (DID) prefix. |
| VDN | See Vector Directory Number. |
| Vector | A list of steps that process calls in a user-defined manner. The steps in a vector can send calls to splits/skills, play announcements and music, disconnect calls, give calls a busy signal, or route calls to other destinations. Calls enter vector processing via VDNs, which may have received calls from assigned trunk groups, from other vectors, or from extensions connected to the switch. |
| Vector directory number (VDN) | An extension number that enables calls to connect to a vector for processing. A VDN is not assigned an equipment location. It is assigned to a vector. A VDN can connect calls to a vector when the calls arrive over an assigned automatic-in trunk group, dial-repeating (DID) trunk group, or ISDN trunk group. The VDN by itself may be dialed to access the vector from any extension connected to the switch. |
| Weekly data | Daily data that has been converted to a weekly summary. |
| Write permission | The CMS user can add, modify, or delete data and execute processes. Write permission is granted from the User Permissions subsystem. |

Write permission

Index

A

| | |
|---|-----|
| accessing data | 60 |
| ACD Shifts database items | 136 |
| Agent database items | 79 |
| Agent Exceptions database items | 98 |
| Agent Group database items | 134 |
| Agent Login/Logout database items | 90 |
| Agent Trace database items | 91 |
| Archiver Execution database items | 133 |

B

| | |
|--|----|
| building an ODBC application | 45 |
|--|----|

C

| | |
|---|--------|
| Call Record database items | 94 |
| Call Work Codes database items | 96 |
| call-based data | 76 |
| circular structure | 73 |
| client connectivity | 60 |
| client support | 24 |
| client trace | 67 |
| CMS | |
| feature interactions | 24, 71 |
| CMS schema | |
| generating | 138 |
| CMS server | |
| installing ODBC | 30 |
| configuration | |
| Solaris client | 41 |
| configuring | |
| ODBC Windows client | 49 |
| server data source | 53 |
| tracing | 57 |
| user data source | 56 |
| Current Day Configuration Forecast database items | 129 |
| Current Day Forecast Report database items | 130 |
| Customer Log database items | 133 |

D

| | |
|---|-----|
| Data Collection Exceptions database items | 102 |
| Data Collection Period database items | 132 |
| data source | |
| disconnecting | 63 |

| | |
|--|-----|
| removing | 57 |
| database | |
| ACD Shifts items | 136 |
| Agent Exceptions items | 98 |
| Agent Group items | 134 |
| Agent items | 79 |
| Agent Login/Logout items | 90 |
| Agent Trace items | 91 |
| Archiver Execution items | 133 |
| Call Record items | 94 |
| Call Work Code items | 96 |
| Current Day Configuration Forecast items | 129 |
| Current Day Forecast Report items | 130 |
| Customer Log items | 133 |
| Data Collection Exceptions items | 102 |
| Data Collection Period items | 132 |
| data types | 77 |
| Database Items | 136 |
| Disk Full Exceptions items | 103 |
| index items | 76 |
| Malicious Call Trace Exceptions items | 101 |
| Split/Skill Exceptions items | 99 |
| Split/Skill items | 103 |
| Synonyms items | 135 |
| table names | 73 |
| tables description | 76 |
| Trunk Group Exceptions items | 99 |
| Trunk group items | 111 |
| Trunk items | 116 |
| VDN Exceptions items | 100 |
| Vector Exceptions items | 101 |
| Vector items | 119 |
| Database Items | 136 |
| database logic structure | 72 |
| debug levels | |
| setting | 35 |
| determining CMS version | 30 |
| disconnecting | |
| data source | 63 |
| Disk Full Exceptions database items | 103 |
| driver administration | 55 |

E

| | |
|----------------------------|----|
| error messages | 69 |
| errors | |
| test application | 68 |

F

| | |
|--------------------------------|-----|
| feature interactions | 71 |
| Forecasting tables | 129 |

G

| | |
|------------------------------------|-----|
| generating CMS schema | 138 |
|------------------------------------|-----|

H

| | |
|--------------------|----|
| helplines. | 15 |
|--------------------|----|

I

| | |
|--|----|
| installing ODBC on CMS server | 30 |
| on Windows client. | 46 |
| over the network | 48 |
| interval-based data | 76 |

L

| | |
|---------------------------------|----|
| log levels setting | 35 |
|---------------------------------|----|

M

| | |
|--|-----|
| Malicious Call Trace Exceptions database items | 101 |
|--|-----|

N

| | |
|-----------------------------------|----|
| network install ODBC | 48 |
| network support | 67 |

O

| | |
|---|----|
| ODBC background and functionality. | 17 |
| data uses. | 20 |
| driver administration. | 55 |
| driver, about | 21 |
| feature interactions | 71 |
| features | 22 |
| installing on server | 31 |
| installing on Solaris client | 37 |
| languages | 22 |
| logins | 22 |
| performance impact | 23 |
| queries | 22 |

| | |
|----------------------------------|----|
| requesting data | 20 |
| server data source | 53 |
| software compatability | 29 |
| turning off | 36 |
| turning on | 36 |

P

| | |
|-------------------------------|----|
| performance impacts | 23 |
|-------------------------------|----|

Q

| | |
|------------------|----|
| queries. | 22 |
|------------------|----|

R

| | |
|-------------------------------------|----|
| relational database model | 19 |
| removing data source | 57 |

S

| | |
|---|-----|
| schema | 138 |
| security, port allocation | 24 |
| server debug levels | 35 |
| server log file | 67 |
| server log levels | 35 |
| server utilities. | 35 |
| software compatibility | 29 |
| Solaris client building an ODBC application. | 45 |
| configuration | 41 |
| installing ODBC | 37 |
| test connectivity | 44 |
| Split/Skill database items | 103 |
| Split/Skill Exceptions database items. | 99 |
| structured query language | 19 |
| supported languages | 22 |
| supported logins | 22 |
| Synonyms database items. | 135 |

T

| | |
|---|----|
| table names | 73 |
| table permissions | 24 |
| tables agent | 72 |
| VDN | 72 |
| test application errors | 68 |
| test connectivity Solaris client | 44 |
| testing connectivity | 60 |
| tracing configuring | 57 |

| | |
|---|-----|
| troubleshooting | 65 |
| Trunk database items | 116 |
| Trunk group database items | 111 |
| Trunk Group Exceptions database items | 99 |

U

| | |
|-----------------------|----|
| user data source | |
| configuring | 56 |

V

| | |
|--|-----|
| VDN Exceptions database items | 100 |
| Vector database items | 119 |
| Vector Exceptions database items | 101 |
| viewing drivers | 59 |

W

| | |
|---------------------------|----|
| Windows client | |
| configuring | 49 |
| installing ODBC | 46 |

