Avaya Aura® Communication Manager Messaging R6.3.100 SP7 (for CM R016x.03.0.141.0) Release Notes

May 10, 2016

Overview

Communication Manager Messaging R6.3.100 Service Pack 7 (SP7) contains several important fixes listed later in this release letter.

Notes:

- Communication Manager Messaging 6.3.100 must be installed prior to applying this service pack.
 Verify the CM Release String in Software Version output of the installed system is R016x.03.0.141.0 prior to downloading and installing this SP.
- Service Pack 7 is cumulative so you do not need to install any previous service packs.
- Installing this service pack as outlined in this document will be service affecting.
- Support for Communication Manager Messaging 6.3, Load 124 (R016x.03.0.124.0) is deprecated, and customers should update to Load 141 (R016x.03.0.121.0). The End of Support date for Load 124 is 30 April 2016.
- For software security consideration, Avaya recommends changing Communication Manager Messaging account passwords at regular intervals, staying current on the latest available Service Packs and patches, and reinstalling Authentication Files periodically to change the local craft password.
- Communication Manager Messaging has updated the Simple Network Management Protocol (SNMP) functionality to Net-SNMP. See PSN020171.
- Avaya has deprecated support for the H.323/Q.Sig integration for Communication Manager Messaging, and is moving to the Avaya SIP integration. Customers should consider changing the Communication Manager Messaging application to the SIP integration. The H.323/Q.Sig integration has been removed with the release of Communication Manager Messaging 7.0.

System Platform

Communication Manager Messaging 6.x Releases and Service Packs are tested with specific versions and updates of System Platform 6.x. For more information, see Communication Manager Software & Firmware Compatibility Matrix at http://support.avaya.com or the appropriate Communication Manager Product Correction Notices.

Avaya has deprecated support for System Platform, and moving to the Avaya Virtual Platform and Virtual Enablement with the release of Communication Manager Messaging 7.0.

Available downloads

Avaya Aura Communication Manager Messaging – System Platform Offer (Install in this order below!)

| File | Description | PLDS File ID | PCN |
|----------------------------------------|------------------------------------------------------------------|--------------|-----------|
| vsp-patch- 6.3.8.01002.0.noarch.rpm | Avaya Aura® System Platform 6.3.8 | CMM70000011 | |
| KERNEL-2.6.18- 409.AV1.tar | Avaya Aura Communication Manager 6.3 Kernel Service Pack 6 | CM000000443 | PCN 1922S |
| PLAT-rhel5.3-3020.tar | Avaya Aura® Communication Manager 6.3 Security Service Pack 7 | CMM70000012 | PCN 1921S |
| 03.0.141.0-22901.tar | Avaya Aura Communication Manager 6.3.114 (Service Pack 114) | CMM63000092 | PCN 1798S |
| CMM-03.0.141.0-0700.tar | Avaya Aura Communication Manager Messaging 6.3 Service Pack 7 | CMM63000094 | |

Avaya Aura Communication Manager Messaging – VMware Offer (Install in this order below!)

| File | Description | PLDS File ID | PCN |
|-------------------------------------|------------------------------------------------------------------|--------------|-----------|
| VMWT-2.6.18-409.AV1-5.5- 001.tar | Communication Manager 6.3 VMWare Tools Service Pack 7 | CM000000444 | PCN 1923S |
| KERNEL-2.6.18- 409.AV1.tar | Avaya Aura Communication Manager 6.3 Kernel Service Pack 6 | CM000000443 | PCN 1922S |
| PLAT-rhel5.3-3020.tar | Avaya Aura® Communication Manager 6.3 Security Service Pack 7 | CMM70000012 | PCN 1921S |
| 03.0.141.0-22901.tar | Avaya Aura Communication Manager 6.3.114 (Service Pack 114) | CMM63000092 | PCN 1798S |
| CMM-03.0.141.0-0700.tar | Avaya Aura Communication Manager Messaging 6.3 Service Pack 7 | CMM63000094 | |

Installation

It is highly recommended that a system backup of the Messaging data set "Messaging Translations, Names and Messages" be performed prior to applying any update. Service Pack 6 is service affecting for the Communication Manager Messaging Application.

Install each of the service packs in the order they are listed in the table using the following procedures.

Applying the Service Pack on System Platform

Apply updates using the method outlined below.

To download:

- 1. Log on to the System Platform Web Console. Use an advanced administrator login and password.
- 2. Click Server Management > Patch Management > Download/Upload.
- 3. From the **Choose Media** list, select the medium to search for a patch.
- 4. Choose the medium specific selections to complete the download.

To install:

- 1. Click Server Management > Patch Management > Manage.
- 2. On the Patch List page, click on the Service Pack ID link to see the details.
- 3. On the Patch Detail page, click Install.

Applying the Service Pack on VMware

To download:

- 1. Log on to the System Management Interface from a bowser.
- 2. Click Administration > Server (Maintenance) > Miscellaneous > Download Files.
- 3. To download files from the system used to access the CMM VM, select **File(s) to download from the machine being used to connect to the VM** and then:
 - a. Click **Browse** or enter the path to the file that resides on the system.
 - b. Click Open.
- 4. To download files from a Web server to the CMM VM, select **File(s) to download from the LAN using URL** and then:
 - a. Specify the complete URL of the file.
 - b. If a proxy server is required for an internal Web server that is not on the corporate network, enter the details in the server:port format.
 - i. Enter the name of the proxy server such as network.proxy or IP address.
 - ii. If the proxy server requires a port number, add a colon (:).
- 5. Click Download.

To install:

1. Click Administration > Server (Maintenance) > Server Upgrades > Manage Updates.

The Manage Updates page displays the list of uploaded service packs.

- 2. Select the Service Pack from the list.
 - a. Click Unpack.
 - b. Click **Continue** to return to the Manage Updates page.
 The status of the selected service pack changes to **unpacked**.
- 3. Select the same patch from the list.
 - a. Click Activate.
 - b. Click **Continue** to return to the Manage Updates page.

The status of the selected service pack changes to **activated**.

Removing the Service Pack

Removing a Service Pack will remove all updates from the system and bring it to a base installation. Note that removing the service pack will leave the messaging system in a stopped state. Manual starting of messaging via the SMI is required to start the voice system. Note a subsequent Service Pack install will automatically start messaging.

Removing the Service Pack from System Platform

- 1. Log on to the System Platform Web Console. Use an advanced administrator login and password.
- 2. Click Server Management > Patch Management > Manage.
- 3. Under the cm section on the Patch List page, click on the service pack ID link to see the details.
- 4. On the Patch Detail page, click Remove.
- 5. Optionally if it is desired to remove the original tar file from the system click **Remove Patch File**. This will remove the service pack tar file from the system.

Removing the Service Pack from VMware

- 1. Log on to the Messaging System Management Interface (SMI).
- 2. Select Administration > Messaging > Utilities > Stop Messaging.
- 3. Click Administration > Server (Maintenance) > Server Upgrades > Manage Updates. The Manage Updates page displays the list of installed service packs.
- 4. Select the service pack from the list.
 - a. Click Deactivate.
 - b. Click **Continue** to return to the Manage Updates page.
 The status of the selected patch changes to **unpacked**.
- 5. Select the same patch from the list.
 - a. Click Remove.
 - b. Click **Continue** to return to the Manage Updates page.

The patch will no longer appear in the list of service packs.

6. After the Service Pack has been uninstalled, do not start messaging until another Service Pack or Patch has been installed since CMM will not function properly when reverted to its base 6.3 installation.

Issues Fixed in SP 7

| | DESCRIPTION |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MSG-22291 | CM's statapp function can not accurately determine whether Messaging is up or down |
| MSG-22334 | SMI Subscriber traffic report for remote components is wrong on SMI (for daily and monthly), but correct on the Fc |
| MSG-22546 | Anonymous authentication allowed for postfix SMTP |
| MSG-22568 | Enhance SMTP configuration options: Allow removal of port 25 from corporate LAN |
| MSG-22600 | Message Delivery fails to local subscriber from remote reply-able ELA list for message initiated by a local subscriber due to authentication required for messages sent by local subscribers |
| MSG-22700 | If an administrative account (dadmin, craft, etc) gets locked-out, the mechanism to notify someone is broken |

| | DESCRIPTION |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MSG-21019 | msgPasswordAllowed may have been corrupted, causing problems with custom Class of Service (CoS). On occasion, the subscriber CoS may change in an unintended way. |
| MSG-21143 | With the Outlook 2010 Address book, the user could encounter "Unknown error" when searching 'Display by Name' on 'Advanced Find'. |
| MSG-21458 | Outlook Address Book Search can fail when there are over 2000 subscribers. |
| MSG-21865 | Changing mailbox number to new mailbox number, then creating a new subscriber with old mailbox number causes Duplicate Mailbox error when the Numeric Address matches the Mailbox number. |
| MSG-21899 | Resent messages generate corrupt mailbox inbox counts if there is an active login for the subscriber. This may also result in an incorrect MWI state. |
| MSG-21961 | Additional encryption on SMTP login mechanisms is required. Security enhancement. |
| MSG-21986 | SMTPS: allow only TLSv1 (not SSLv3) protocol. Security enhancement. |
| MSG-22000 | SMTP: Remove support for anonymous SSL/TLS ciphers. Security enhancement. |

| MSG-22093 | Reserved space on forwarded Call Answer messages not reclaimed, so cornerstone platform layer think the system is out of space until an spDskMgr restart. |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| MSG-22116 | When a remote subscriber on an LDAP node has an email change, the MboxName attribute is usually changed instead of the Mail attribute. |
| MSG-22199 | Can't see all the IIM logs contents (e.g. some email addresses) in MS IE because it interprets <x> as an X tag instead of data.</x> |

| | DESCRIPTION |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MSG-14550 | SMI allows changing mailbox number to its secondary extension, which is invalid. |
| MSG-18644 | Various Voice-Name audit issues, which need to be corrected during the audits. |
| MSG-18773 | SMI auto-attendant: no error when editing automated attendant menu to transfer to an invalid variable length extension. |
| MSG-18888 | AE_SYSERR when changing a primary and secondary extensions to the same value, which is not a valid error. |
| MSG-18915 | IMAP Status does not correctly reflect number of currently running client sessions. |
| MSG-19042 | imapd does not handle all IPv6 co-resident addresses correctly. |
| MSG-19147 | mm audit mishandles valid audio formats. |
| MSG-19625 | Eliminate Adata core due to invalid XML forwarding rules. |
| MSG-19802 | Messages not forwarded due to incoming mailbox rules. |
| MSG-19917 | Idap_full_upd status from MN is not handled properly. |
| MSG-19073 | Ldap FEs shouldn't return empty umRecordedName attribute value. |
| MSG-20044 | TUI: Subscriber Admin Menu: No option to: "Disable Message Delivery" unless Call-Answer-Disabled is also enabled |
| MSG-20062 | If PIN is too small and the Minimum time between PIN changes is not yet passed, TUI forces a change of PIN, but Adata rejects change and TUI says "This call experiencing difficulties" |
| MSG-20114 | Transfers Stop Working Every Few Days. Restart Messaging to Fix. |
| MSG-20200 | Automatic Forwarding of outside Call Answer Messages uses an invalid 'Mail From' address. |
| MSG-20257 | Eliminate SSL vulnerability for IMAP4, POP3 and LDAP. |
| MSG-20366 | Removing networked machine, run network data audit to tombstone subscribers, and weekly audit to remove on AAM, subscribers removed on MN; also fixes removal of remote subscribers by other means. |
| MSG-20506 | Can not disable standard LDAP port. |
| | |

| MSG-20524 | postfix can lose Certificate Chain File on postfix restart |
|-----------|--------------------------------------------------------------------------------------------------------------------------------|
| MSG-20565 | Outlook 2010: Address Book: searching for users only works using 'Advanced Find', Regular: 'Search' Fails with 'Unknown Error' |
| MSG-20739 | Can not add an email address to an ELA list |
| MSG-20804 | After shutting down abnormally, LDAP may come up in a corrupt state. |
| MSG-20850 | SMTP Log Summary report only gives 4 dates to select from. |
| MSG-20875 | From: address malformed on an auto-forwarded message from an ELA list. |
| MSG-20917 | "Can't bind to Unix Socket: No such file or directory" error message on console during startup/shutdown |
| MSG-21043 | Messaging setting incorrect SIP domain in P-AI header for MWI NOTIFY message |
| MSG-21094 | Generated Mime versions of Priority Call Answer Messages do not have any Priority Headers. |
| MSG-21189 | Imapd SSL_write() errors are handled incorrectly. |
| MSG-21356 | Message Core fails to start when FIPS mode is enabled on JITC CMM-FM. |
| MSG-21539 | TUI disconnects with "This Call Experiencing Difficulties". |
| MSG-21620 | Restore fails due to multiple copies of the OcTime LDAP attribute. |

| | DESCRIPTION |
|-----------|------------------------------------------------------------------------------------------------------------------------------|
| MSG-16451 | Imapd core dump when using the proprietary Monitor extension. |
| MSG-16509 | Outcall attempt could prevent ports from taking calls. |
| MSG-13962 | MsgCore does not follow RFC2156 when sending out a private message. |
| MSG-17791 | SMI Edit Subscriber web page incorrectly using Max Retries instead of ErrAllow to determine when a mailbox should be locked. |
| MSG-17881 | MCAPI server_sync_message doesn't allow a year larger than 2015. |
| MSG-17752 | Allow postfix generated DSNs to include larger messages. |

| MSG-18019 | IRAPI changes to support ILG answer capabilities (ChannelDispatch). |
|-----------|----------------------------------------------------------------------|
| MSG-18281 | SipAgent and T38Fax cores are generated on ILG under traffic. |
| MSG-18488 | Drop call when trying to log into mailbox from AA with FIPS enabled. |

| | DESCRIPTION |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| MSG-14355 | Message Core slow to start up. |
| MSG-14482 | IMAP/SMTP Messaging logs help does not display |
| MSG-14371 | Add/Edit Local/Networked Server help incorrect. |
| MSG-14481 | System displays error although date and time set properly in Subscriber Activity log. |
| MSG-14524 | Incoming email through a gateway to mailboxnumber@alias rejected because postfix thinks it is being used as a relay. |
| MSG-14835/MSG-14928 | Voice-Mail delivery from a subscriber to a subscriber with a full mailbox does not behave correctly. |
| MSG-14814 | Fresh installation: Messaging startup never completes. |
| MSG-14898/MSG-15099 | Messages to mailbox with Fowarding rule whose destination handle matches a local mailbox number, are resent to both the destinations. |
| MSG-14983 | Email address field could be set to an invalid email address. |
| MSG-15153 | Cannot change category order from 'nuo'. |
| MSG-15580 | Changes from MSG-14983 cause remote updates to fail. |
| MSG-15544/MSG-15638 | Imapd core dumps regenerating a non-MIME Message. |
| MSG-15672 | Imapd loses user-defined keywords when a folder has more than 64 messages. |
| MSG-15425 | LDAP networking connection failed with IPv6. |
| MSG-16052 | Remove support for IALX migrations. |
| MSG-16092 | Subscribers are missing after upgrade from CMM6.2 to CMM6.3 on MES due to multiple UserName attributes. |
| MSG-16094 | CMM responds to MWI NOTIFY with OK instead of error. |
| MSG-14814 | On a fresh install, messaging may fail to start after service pack installation and Switch Link admin. |
| MSG-14559 | VMware: CMM switch integration may allow one to have more CA ports than UDP ports, thus calls fail. |

| MSG-13738/MSG-13935 | Messaging SIP TLS ciphers and connection methods need to change to support CM TLS interface changes. |
|---------------------|-------------------------------------------------------------------------------------------------------------|
| MSG-14937/MSG-14947 | Connection between one Application and SM is down in cluster 2 Applications and 1 MSS when running traffic. |
| MSG-14948/MSG-14999 | SIP TLS audit does not run. |
| MSG-15063/MSG-15082 | SipAgent core dump, channels showed Manoos. |
| MSG-15366 | SIP TLS handshake between embedded CM and CMM failed. |
| MSG-15918 | CMM backups in FIPS mode time out. |
| MSG-16052 | Remove support for IALX migrations. |
| MSG-16168 | Silence happened when system read header of a message from a 18-digit mailbox. |

| | DESCRIPTION |
|-------------------------|------------------------------------------------------------------------------------------------------------|
| MSG-11623 | Text to speech is not working , Getting silent on text messages. |
| MSG-13755/MSG- 13802 | Call transfer fails if CM has SEMT(SIP Endpoint Managed Transfer) enabled. |
| MSG-13728/MSG- 13860 | CMM is failing to handle a shuffling scenario correctly. |
| MSG-11385/MSG- 14092 | SipAgent crashed few times under load test. |
| MSG-14382 | Setup capacity maximums (call answer ports, etc.) for CMM on VMware. |
| MSG-10582 | Recorded name of some subscribers is played incorrectly after migrating. |
| MSG-13376/MSG- 13429 | Non-English MessagingLocale invalid after restore of data from CMM6.2 or greater database. |
| MSG-13490/MSG- 13492 | email Messages not properly parsed when Mime Component Header has a line after boundary definition. |
| MSG-12134/MSG- 13619 | LDAP/SMTP Networking: Outgoing Delta Updates have lots of issues - including bulk add (e.g.via Provision). |
| MSG-13635/MSG- 13767 | Adata does not release the RunToken when looking up LDAP FE ports (Ldapcorp etc). |
| MSG-13035/MSG- 13771 | Password history does not remember initial PIN for a new user. |
| MSG-13953 | Fix typo 'Attrubutes' in audixupg. |
| MSG-13920 | Remove switch ID from subscriber page and add MWI Enabled? field. Switch Id changes on upgrades/restores. |
| MSG-14136 | Change MailboxNumber generates system error when Secondary Extension is defined. |

| MSG-14242 | Improve topstat output. |
|-----------|--------------------------------------------------------------------------------------|
| MSG-14195 | Vsc uses up all the file descriptors (libAnnMgr bug). |
| MSG-14257 | Email for local users (e.g. cron, root) can get delivered to the customer's network. |
| MSG-13695 | LDAP database corruption during scheduled backup. |
| MSG-14280 | Add entries to adata_utp to add/get/delete extswid data. |
| MSG-13651 | Unable to send messages to mail gateway when no MX record. |

| | DESCRIPTION |
|-------------------------|------------------------------------------------------------------------------------------------|
| MSG-12361/MSG- 12362 | MsgCore core dump in libmcapi.so: memcpy() copying beyond source from unmapped virtual memory. |
| MSG-12466/MSG- 12630 | There shouldn't be any alarms on SMI when doing de-activate/re-activate of CM Service Pack. |
| MSG-11296 | CMM License Utilization Reporting to WebLM |
| MSG-12830/MSG- 12903 | Large messages cannot be delivered via SMTP. |
| MSG-12945/MSG- 13017 | While playing an announcement (ann id 1 or 995), Vsc core dump. |
| MSG-13129 | Message with maximum length cannot be sent on TUI with "Nothing to approve" prompt. |

| | DESCRIPTION |
|-------------------------|--------------------------------------------------------------------------------------------------------------|
| MSG-10852/MSG- 11051 | Change Idap default password failed when using special characters |
| MSG-10255/MSG- 11183 | Trusted server's password is not saved when it contains a space, even though the SMI says it was successful. |
| MSG-11054 | Can't edit Auto Attendant Menu after deleting a subscriber which is in menu. |
| MSG-11193 | After migration from LX1.0 or 2.0 slurpd core dump. |
| MSG-11300 | Subscriber could be created with "Email" exceed more than 64 characters. |

| MSG-10530 | User gets dead air when transferring to extension which covers back to messaging. |
|-------------------------|---------------------------------------------------------------------------------------------------|
| MSG-11062/MSG- 11240 | Call transfers could eventually happen on channel 0 after exhausting the block of transfer ports. |
| MSG-11306 | SM 11 alarm was raised and SM core dump. |
| MSG-11312/MSG- 11370 | SipAgent memory leak with invalid switch config |